

SP585 Closet Pole Sockets

- Flange design prevents accidental knock out of pole.
- Made from wrought steel.
- Accommodates pole or pipe with outside diameter of 1-3/8".
- Packed in pairs.

Finishes	
Ives Numbe	I

Ives Number	F3	
BHMA	632	



SP586 Closet Pole Sockets

- Made from a heavy duty plastic for long life and extra strength.
- Single screw mounting.
- Accommodates pole or pipe with outside diameter of 1-3/8".
- Packed in pairs.

Finish

White Plastic



Meets ANSI/BHMA A156.16

07 **Window Lock**

- Designed low to the sash for superior strength and greater resistance to breakage.
- Vertical and horizontal camming action for snug, non-rattling fit.
- Heavy gauge springs provide long-wearing action.
- Made from solid brass, aluminum, or epoxy coated aluminum.

Dimensions

Base: 15/16" x 2-9/16" Strike: 5/8" x 2-9/16"

Finishes brass

	_						
Ives Number	В3	B15	B15A*	B26	B26D	B716	
BHMA	605	619	620	625	626		

Finishes aluminum

Ives Number	А3	A5*	A10B	A14	A15	A92	A-716	A-W	A-BLK	
BHMA	666		703	669	670	673				

^{*} only available in Schlage Carded or Slim-Pak of 25





Meets ANSI/BHMA A156.16

90 Side Window Lock

- · May be used singularly for small windows or in pairs for large windows.
- · Cam action eliminates rattles and holds window firmly in desired position.
- Made from aluminum.

Dimensions

1-3/4" High x 1-1/8" Wide

Finishes

Ives Number	А3
ВНМА	666



Meets ANSI/BHMA A156.16

026 Bar Window Lift

- · Facilitates opening of window in a safe manner.
- Can also be used as a drawer or utility pull.
- Made from solid brass, aluminum, or epoxy coated aluminum.

Dimensions

Base: 1-1/8" High x 4" Wide Projection: 1-1/16"

Finishes brass

Ives Number	В3	B5	B15	B15A*	B26	B26D	B716	
BHMA	605	609	619	620	625	626		

Finishes aluminum

I misnes atominom									
Ives Number	А3	A5	A14	A15	A92	A716	A-W	A-BLK	
ВНМА	666		669	670	673				

^{*} only available in Schlage Carded or Slim-Pak of 25



Meets ANSI/BHMA A156.16

066 Casement Fastener

- For use on windows to provide weather-tight fastening and security.
- Also ideal for securing louvered doors and small doors.
- · Made from solid brass or aluminum.
- Specify: Surface, Strike (SS)

Rim, or Strike (RS)

Mortise Strike (MS)



Dimensions

Base: 1-5/8" x 7/8" Projection: 1-3/8"

Finishes brass

Ives Number	B3	B5	B15	B26	B26D			
ВНМА	605	609	619	625	626			
Finishes aluminum								
Ives Number	А3	A5	A10B	A14	A92			
BHMA	666	668	703	673				



Meets ANSI/BHMA A156.16

66 **Casement Fastener**

- For use on windows to provide weather-tight fastening and security.
- Also ideal for securing louvered doors and small doors.
- Made from solid brass or aluminum.
 - Specify: Surface, Strike (SS)

Rim Mortise Strike (RS)



Dimensions

Base: 2-1/16" High x 1-1/16" Wide Projection: 1-7/8"

Finishes brass

	_						
Ives Number	B3	B5	B15	B26	B26D	B716	
ВНМА	605	609	619	625	626		

Finishes aluminum

i iiiisiies aton	i ii ii sii es atommorn								
Ives Number	А3	A5	A14	A92					
ВНМА	666		669	673					



71 **Casement Adjuster**

- Securely holds casement window in any position.
- Can also be used to hold cabinet lids and drafting table tops in various positions.
- Made from burnished steel or solid brass.
- Available in 10" and 12" lengths.

Dimensions

Tube: 3/8" x 5/8" Projection: 1"

Sash Plate:

Brass: 1-5/8" High x 5/8" Wide Steel: 2 x 5/8" Wide

Sill Plate:

2-1/4" x 15/16" Wide

Finishes brass

Ives Number	В3	B26	
BHMA	605	625	