



Sika® ORGILL® Product Catalog



Fill Joints & Gaps

Sikaflex® Self-Leveling Sealant

Fast curing, self leveling PRO grade polyurethane elastic sealant for sealing expansion joints, gaps and moving cracks in horizontal concrete and masonry. **No tooling required** – levels itself!

Color / Size	Orgill SKU #	Sika SKU #
Gray / 10.1 oz.	3448438	515304
Gray / 29 oz.	0589994	515302
Sandstone / 29 oz.	4145397	515282

BONDS TO NEW CONCRETE 24HRS AFTER CURE

24HR GREEN | **1HR WET**

CAN BE APPLIED TO WET CONCRETE AFTER 1HR



Sikaflex® Construction Sealant

Elastic polyurethane construction sealant for sealing expansion joints, gaps, construction joints, windows, doors and siding. Ideal bedding sealant for door and window installations.

Color / Size	Orgill SKU #	Sika SKU #
Limestone / 10.1 oz.	9193780	515308
White / 10.1 oz.	1214196	515309
Dark Bronze / 10.1 oz.	1019678	515310
Capitol Tan / 10.1 oz.	9796749	515311
Aluminum Gray / 10.1 oz.	5855812	654546

BONDS TO NEW CONCRETE 24HRS AFTER CURE

24HR GREEN | **1HR WET**

CAN BE APPLIED TO WET CONCRETE AFTER 1HR



Limestone White Dark Bronze Capitol Tan Aluminum Gray

Colors are a visual representation only. Use actual cured samples for color matching.

Sika® Backer Rod

Use to partially fill deep joints or cracks prior to sealant application. Helps prevent sealant from bonding to three sides of the joint or crack, which can limit movement capability of sealant.

Color / Size	Orgill SKU #	SIKA SKU #
Gray / 3/4 in.	7874530	108130



Sikaflex® Mortar Fix

"FIX IT ONCE" with this PRO grade polyurethane elastic mortar joint filler for repairing cracked and split mortar joints between brick, masonry, and stone. Textured to match concrete surface.

Color / Size	Orgill SKU #	SIKA SKU #
Limestone / 10 fl. oz.	2238541	515313

BONDS TO NEW CONCRETE 24HRS AFTER CURE

24HR GREEN | **1HR WET**

CAN BE APPLIED TO WET CONCRETE AFTER 1HR




Repair Cracks

Sikaflex® Concrete Fix

"FIX IT ONCE" with this PRO grade polyurethane elastic joint filler for repairing cracks in vertical and overhead concrete surfaces. Exceptional cut and tear resistance.

Color / Size	Orgill SKU #	SIKA SKU #
Gray / 10.1 fl. oz.	0512830	515318



Sikaflex® Crack Flex Sealant

One-component polyurethane sealant for repairing horizontal cracks in concrete up to 1" wide. Textured for added density and gradually self levels into cracks. Flexible, elastic and waterproof.

Color / Size	Orgill SKU #	Sika SKU #
Gray / 10.1 fl. oz.	1214212	515306



Sikadur® Crack Fix

Two-component, 100% solids, moisture-tolerant, low-viscosity, high-strength, multi-purpose, epoxy resin adhesive.

Color / Size	Orgill SKU #	SIKA SKU #
Clear Amber / 10.1 fl. oz.	7002876	107655



Post Installation

Sika® PostFix®

Sika Fence Post Mix is a two component, pre-proportioned polyurethane resin. It mixes in the bag to produce expanding foam for supporting and backfilling fence, mail box, gate and signage posts. One pouch replaces two 50 lb. bags of concrete mix. Sets in as fast as 3 minutes with no water or special tools required. **NOT FOR STRUCTURAL POSTS.**

Color / Size	Orgill SKU #	Sika SKU #
Light green / 33 fl. oz.	1019686	483503



Bonding & Fortifying

SikaLatex R® Concrete Bonding Adhesive

Bond new concrete to old with this pro grade acrylic latex. Add directly to the concrete mix for superior strength and durability. Does not re-emulsify in immersed conditions like other brands.

Color / Size	Orgill SKU #	Sika SKU #
White / 1 gal.	1690031	187782
White / 1 qt.	1214220	471643



Bond & Anchor

SikaBond® Construction Adhesive

Multi-purpose polyurethane construction adhesive that bonds to most building materials, including concrete, masonry, wood, glass, metal, porcelain, and tile. Can be permanently submerged in water after cure. USDA approved, ideal for aquatic landscaping.

Color / Size	Orgill SKU #	Sika SKU #
Gray / 10.1 fl. oz.	2326965	106403
Gray / 29 fl. oz.	1214204	505423



Sika AnchorFix®-1

Fast-setting and high strength anchoring adhesive for common anchoring projects such as dowels, bolts, rebar. Unlike epoxies, can be used down to 14°F.

Color / Size	Orgill SKU #	Sika SKU #
Gray / 10.1 fl. oz.	7034069	112729



Sika AnchorFix®-2

Fast-setting and super strong anchoring adhesive for anchoring projects requiring higher strengths such as handicap rails. Exhibits high load capacities and can be dispensed in all types of weather conditions. Unlike epoxies, can be used down to 14°F.

Color / Size	Orgill SKU #	Sika SKU #
Gray / 10.1 fl. oz.	0252346	112718



Patching

Sikacryl® Ready-Mix Concrete Patch

Ready-to-use acrylic-based patcher for repairing small vertical or horizontal cracks and spalls in concrete and masonry. Fully cures in 24 hours to a tough and durable finish.

Color / Size	Orgill SKU #	Sika SKU #
Light Gray / 1 qt.	1214238	472189
Light Gray / 1 gal.	1019694	514899



Sikacryl® Ready-Mix Stucco Patch

Easy to use, stucco patch for repairing small spalls and cracks in stucco. This acrylic based stucco patch can be used on masonry surfaces, exterior finish foundation and more. One quart covers approximately 100 sq. ft.

Color / Size	Orgill SKU #	Sika SKU #
Off White / 1 qt.	1214261	503333



Patching

SikaQuick® Patch

An easy to use, mix-in-the-bag, fast curing patch for repairing holes/spalls in concrete. This two-part, pre-proportioned cementitious mix can be used to repair concrete basement floors, driveways, patios and more. Unit yields approximately 1 sq. ft. at a 1/2 inch depth.

Color / Size	Orgill SKU #	Sika SKU #
Gray / 29 fl. oz.	1214253	535570






Grouting

SikaGrout® 212

High performance, non-shrink grout for structural grouting of columns, posts, railings, bolts, anchor rods, fences, etc. Flowable formula for easy placement.

Color / Size	ORGILL SKU #	SIKA SKU #
Gray / 50 lb. bag	0701813	90824



Flooring Levelers

SikaLevel® Self-Leveling Underlayment (Primer)

A one-component highly fluid, durable cementitious underlayment for interior concrete, and cementitious substrates. It can be applied manually or by pump to produce a self-smoothing, rapid-setting, flat and economical substrate prior to the application of a final floor finish. Typical application thickness is 1/25 to 2 inches* (1 to 50 mm). Make sure to prime substrates before the application of SikaLevel Self Leveling Underlayment using SikaLevel Primer (A one-part solvent-free, acrylic-based solution).

Color / Size	Orgill SKU #	Sika SKU #
SLU/Dark Gray / 50 lb.	1214295	517004
Primer/White / 1 gal.	1214279	517003



Sika Sales Representation

Jones Sales & Marketing Group • Mike Newman • P. 770.880.2592
mnewman@jonessalesandmarketing.com

Sika Key Account Manager • David Paine • paine.david@us.sika.com

For Customer Service/Technical Service, contact 800.933.7452

For the most current Product Data Sheet and Material Safety Data Sheet, visit usa.sika.com/retail

