

Specialty


Strong-Drive® SCN SMOOTH-SHANK CONNECTOR Nail

For Simpson Strong-Tie® Connectors

Simpson Strong-Tie Connector nails are the best choice for Simpson Strong-Tie connectors.

See p. 158 for collated Strong-Drive SCN Smooth-Shank Connector Nails.

For Technical Data and Loads, see p. 338




Hot-Dip Galvanized – Class D

Model No. Prefix	Length (in.)	Gauge	Shank Diameter (in.)	Head Diameter (in.)	Approx. Count per lb.	1 lb. Model No.	1 lb. Box Model No.	5 lb. Box Model No.
N8	1 1/2	10	0.131	0.31	147	N8	N8DHDG-R	N8D5HDG-R
N10	1 1/2	9	0.148	0.31	120	N10	N10DHDG-R	N10D5HDG-R
10D	3	9	0.148	0.31	50	—	10DHDG-R	10D5HDG-R
16D	3 1/2	8	0.162	0.34	40	—	16DHDG-R	16D5HDG-R

PVC Trim-Board Nail

Specifically designed for use with PVC trim board. The spiral shank beginning of the nail allows the nail to smoothly work itself into the board. The ring-shank provides holding power. Nails that are fully ring shank can blast open the back of a trim board leading to a looser fit, while smooth nails or trim nails do not have the same holding power or strength. The PVC trim-board nail is the best of both worlds.



Type 316 Stainless Steel

Penny Size	Length (in.)	Screw Size/ Nail Gauge	Shank Dia. (in.)	Head Dia. (in.)	Shank	Head Type	Point	Count per lb. (approx)	Package Size	Model No.
8d	2 1/2	13	0.092	0.21	Spiral/Ring shank	Checkered head	Diamond point	196	1,000	T8VTN1000



White