



Meets ANSI/BHMA A156.16

### 40 Decorative Surface Bolt

- Concealed screw design enhances appearance and security.
- Exceptional strength and durability provided by interlocking construction of heavy gauge track and rod.
- Permanent stop prevents rod disengagement from track.
- Tension spring holds bolt in desired position.
- Track assures smooth operation and interlocks with side edges of rod to eliminate marring.
- Decorative 5/8" diameter knob designed to facilitate bolt operation.
- Made from extruded brass or aluminum.
- Available in 3", 4" and 6" lengths.
- Packed with both Universal and Mortise Strikes. Optional Surface Strike available.

#### Dimensions

Throw: 15/16"  
 Projection: 3/4"  
 Width: 11/16"  
 Length: 3, 4 or 6"

#### Finishes *brass*

Ives Number	B3	B5	B10B	B15	B26	B26D
BHMA	605	609	613	619	625	626

#### Finishes *aluminum*

Ives Number	A3*	A15*	PA28	A716*
BHMA	666	670	628	

\* only available 3" bolt Schlage Carded.

A  
Hinges & Pivots

B  
Pulls & Plates

C  
Flush Bolts & Coordinators

D4  
Latches, Catches & Bolts

E  
Stops

F  
Exterior Hardware

G  
Miscellaneous Hardware