

Over 60 years of Electric Fence Experience.



The Dare Way.

Since 1946, Dare has withstood the test of time, by doing what we've always done best—manufacturing a full line of quality electric fencing equipment and other related products.

Our philosophy is simple—continue manufacturing quality products to enhance the long term customer relationships we have developed right from the beginning. Utilize and maintain a knowledgeable and dedicated workforce and sales team. Strive to be the industry leader in product quality and innovation.

And above all, guarantee overall customer satisfaction... That's the Dare way!

- **2 ELECTRIC FENCE ENERGIZERS**
- **3 O.K. CORRAL KIT**
- **4 GATE HANDLES AND GATE HARDWARE**
- **5 INSULATORS**
- **12 FASTENERS AND CLIPS**
- **13 ELECTRIC FENCE POSTS**
- **14 ALUMINUM ELECTRIC WIRE**
- **14 EQUINE PRODUCTS**
- **17 POLYTAPE AND POLYWIRE ACCESSORIES**
- **19 HIGH TENSILE FENCE SUPPLIES**
- 22 SPLICING EQUIPMENT
- 25 ELECTRIC FENCE TESTERS AND MISCELLANEOUS PARTS
- **26 INSTALLATION ACCESSORIES**
- 27 PANS AND PAILS
- **28 FARM TANK FLOAT VALVES**



Includes everything needed to put up a small electric fence in order to safely keep small nuisance animals out of unwanted areas, such as gardens, flower beds, trash containers and more. Ideal for a small garden needing protection from rabbits, raccoons, and pets.

YOUK

ELECTRIC FENCE KIT

ENCE KIT

len

COMPLETE KIT INCLUDES:

- 10 Fence Posts (3466)
- DE 20 Electric Fence Energizer (DE 20)
 - 250' Heavy Duty Polywire (3467)
- 1 Ground Rod with Clamp (2303 & 3469)
 - 3 Split Bolt Wire Connectors (2083-3)
 - 15' x 18 Gauge Hook-Up Wire (3468)
 - 1 Fence Tester (460)

ITEM NO. DEGK 20 How Does Your Garden Grow Electric Fence Garden Kit • 1 to counter pkg • 2 to shipper • 16 lbs.

ELECTRIC FENCE ENERGIZERS

Dare Products' wide range of high performance Electric Fence Energizers. All Dare energizers use **ULTRA LOW OR LOW IMPEDANCE** technology with these standard features:

- Modular circuitry for fast and easy service
- All weather construction for longer life
- Peak Joule output under the most difficult fence conditions
- Two year OTC warranty including lightning damage on most models
- Built in lightning protection
- UL and CSA approved on most models
- Designed and assembled in USA

ENFORCER—110 Volt Models

Best value! Provides the most output for each dollar spent. Use where electrical power source is available—only costs pennies a day to operate. When possible, 110 volt models are always the first choice.

Estimates for Overgrown Fence

| Model 110 Volt | Energy Output (In Joules) | Acres Controlled (Up to) | Outperforms 110 Volt Energizers rated at |
|-------------------|------------------------------|-----------------------------|---|
| DE 20 | .05 | 1 | 1-2 Acres |
| DE 60 | .10 | 3 | 2-5 Acres |
| DE 80 | .20 | 5 | 5-10 Acres |
| DE 120 | .30 | 20 | 5-10 Miles |
| DE 200 | .50 | 50 | 10-15 Miles |
| DE 300 | .75 | 75 | 15-20 Miles |
| DE 400 | 1.0 | 100 | 20-30 Miles |
| DE 600 | 1.5 | 150 | 30-50 Miles |
| DE 1200 | 3.0 | 300 | 50-75 Miles |
| DE 2400 | 6.0 | 600 | 75-100 Miles |
| DE 4000 | 10.0 | 1000 | 100-150 Miles |
| DE 6400 | 16.0 | 2000 | 150-200 Miles |



SENTRY—6 and 12 Volt Battery Models

Better value! Provides more output for each dollar spent. If an electrical power source is not available, the external 12 volt rechargeable battery model is a great alternative.* Deep cycle batteries recommended.

Estimates for Clean Multi-Wire Fence

| Model 6-12 VoltEnergy Output (In Joules) | | Acres Controlled (Up to) | Outperforms Battery Energizers rated at | |
|--|------|-----------------------------|--|--|
| DSB 100 | 0.25 | 25 | 5-15 Miles | |
| DS 140 | 0.35 | 35 | 5-10 Miles | |
| DSX 140 | 0.35 | 35 | 5-10 Miles | |
| DS 300 | 0.75 | 75 | 10-20 Miles | |
| DS 400 | 1.0 | 100 | 20-30 Miles | |
| DS 800 | 2.0 | 200 | 30-50 Miles | |

*Battery not included

Energizer repair parts for all models are available. Please contact Dare for more information.



DE 120

DE 200

DE 2400 DE 4000 DE 6400

> DE 300 DE 400 DE 600 DE 1200

ECLIPSE—6 and 12 Volt Solar Battery Models

Great value! The 6 or 12 volt solar energizer is ideal for use in remote areas where an electrical power source is not available. This model has a self-contained battery and may be preferred for its convenience.

Estimates for Clean Single Wire Fence

| Model | Volt | Energy Output (In Joules) | Acres Controlled (Up to) | Outperforms Solar Battery Energizers rated at |
|--------|---------|------------------------------|-----------------------------|--|
| DS 20 | 6 Volt | .06 | 10 | 1-3 Miles |
| DS 40 | 12 Volt | .10 | 40 | 5-10 Miles |
| DS 100 | 12 Volt | .25 | 100 | 10-25 Miles |
| DS 200 | 12 Volt | .50 | 200 | 25-50 Miles |



Two Year Over the Counter Warranty

Dare Products warrants all fence energizers to the original purchaser for a period of two (2) years from the date of purchase, when installed in accordance with the installation instructions. You must retain your receipt for proof of purchase. This warranty also covers damage to the energizer caused by lightning and voltage spikes.



O.K. CORRAL KIT

Completely portable and easy to set up. Contains everything needed to build a 2500 sq. ft. corral. Includes posts, gates, fasteners, stakes, polywire, tester and battery operated fencer. (4 "D" cells required - not included.) Durable carrying bag attaches to saddle. Ideal for trail riding, hunting and camping trips, horse shows, pasture rotation or any temporary containment situation.

ITEM NO. 2700 • 1 to counter pkg • 3 to shipper • 37 lbs.

KIT INCLUDES:

- 1 DS140 Fence Energizer Requires 4 "D" batteries (not included) or 6-12 volt external battery
- 12 54" Fiberglass posts (In 3 pieces)
- 1 Spool polywire 262'
- 25 Round Post insulators
- 4 Corner stakes and tie down cords
- 2 Gate hooks w/connecting hardware
- 1 24" ground rod/energizer holder
- 1 Roll fluorescent flagging tape



GATE HANDLES AND GATE HARDWARE

OLD IRONSIDES®

These features make OLD IRONSIDES® better:

• Safety hook and body formed as one...from 7/8" diameter steel pipe. • Spring mechanism consists of 41/4" long compression spring fastened to a 5/16" diameter eyebolt. • All metal parts permanently assembled using 20 tons of force. No flimsy snap-on/push-on fasteners used anywhere. • Large insulating grip measures 51/8" long with a 21/4" diameter flange for extra shock protection. Molded of a soft flexible material that will not chip, crack or break when abused. • Performs in any climate. Metal parts plated to resist rust. Molded grip contains carbon black to deter UV rays.

ITEM NO. 1793 • 10 to inner carton • 50 to shipper • 39 lbs.

RUB'RGATE[®] Don't be shocked - be safe - with RUB'RGATE electric fence spring gate handle. Hard hat yellow.

RUB'RGATE soft pliable rubber outer case internally reinforced with semi-rigid, non-conductive vinvl inner tube. This provides a firm grip and acts as an extra layer of insulation. Generous, sensibly spaced flanges allow plenty of hand room. Large, heavy stamped steel plated safety hook. Enclosed spring stretches 31/2" to keep wire taut.

ITEM NO. 1247 • 10 gates to pkg • 5 pkgs (50) to shipper • 15 lbs.

'OLD FAITHFUL' [™] High quality, hi-impact styrene insures long and trouble-free life. Measures 4³/₄" between flanges. All metal parts plated. Heavy stamped steel hook. Enclosed spring stretches 31/2" to keep wire taut. Red.

ITEM NO. 503 • 10 gates to pkg • 5 pkgs (50) to shipper • 13 lbs.

GATE ANCHOR KIT for Wood Post and T-Post. Consists of: two #2238 anchors. two #2249, nails, and two #2550 insulators. (Gate handle not included). ITEM NO.3230 • Individually packed • 10 to shipper • 4 lbs.

SLINKY GATE Stretches to fit gate opening up to 20 feet. Retracts to keep gate off ground when open. Electrified when closed, neutral when open. Highly visible and effective. SLINKY GATE assembly consists of: One Rub'Rgate handle, one large galvanized spring, two pinlock style wood post insulators with galvanized nails, two pinlock style T-Post insulators, one anchor/activator, one fence line clamp/tap and complete schematic instructions. Equipped to fit wood post or T-Post openings.

ITEM NO. 2222 • Individually packed • 5 to shipper • 12 lbs.


BUNGEE STYLE GATE Safe for horses and all livestock. Stretches to fit openings up to 20 feet. Hardware included for both Wood and T-Posts. ITEM NO. 2950 • Individually packed • 5 to shipper • 6 lbs.



The heaviest, toughest DARE electric fence gate handle ever.












ROWND UP LATCH SINGLE One way universal gate latch. Works on wood, tube, galvanized metal, chain link, ornamental and more. Self latching one handed operation, locks securely with or without padlock.

ITEM NO. 3258 • Individually packed • 6 to shipper • 15 lbs.



INSULATORS

powder coated finish.

ROUND POST INSULATORS

DESIGNED TO PERFORM WITH SOLID STATE **ELECTRIC FENCE SHOCKERS**

WESTERN® SCREW-TIGHT for round posts. Fits 1/4" to 9/16" diameter posts and 5/8" fiberglass T posts. Extends wire 1" from post. Installs without tools. Adjustable while current is "on". High density polyethylene with UV inhibitors. Yellow. ITEM NO. WESTERN-RP-25 • 25 to pkg • 20 pkgs (500) to shipper • 26 lbs. **ITEM NO. WESTERN-RP-25W** SAME AS ABOVE - WHITE ITEM NO. WESTERN-RP-25B SAME AS ABOVE - BLACK

ITEM NO. 2936-25 • 25 to pkg • 10 pkgs (250) to shipper • 13 lbs.

WESTERN-RP-25

3260



LARGE WESTERN[®] FOR SUCKER RODS and other oversized round posts.

Fits 1/4" to 7/8" dia and 5/8" fiberglass T-Posts. Holds all wire, polywire, polyrope and polytape up to 11/2". Yellow.


ITEM NO. XLRP-25 • 25 to pkg • 10 pkgs (250) to shipper • 17 lbs. ITEM NO. XLRP-25W SAME AS ABOVE - WHITE ITEM NO. XLRP-25B SAME AS ABOVE - BLACK





Pat. No. 6,353,187

Premium line, offering life-time warranty. Pewter.



WOOD POST INSULATORS

SNUG[®] **1728 INSULATOR** for wood posts. Extends wire 1" from post. Flexible base fits round and flat sided posts. Single headed nails supplied. Molded of high density polyethylene with UV inhibitors. Yellow.

ITEM NO. 1728-25 • (complete with nails) • 25 to pkg • 20 pkgs (500) to shipper • 14 lbs.



Extends wire 1" from face of post. Pat. No. 4, 599, 488

SNUG®-SWP-25 SNUG WOOD POST INSULATOR

Extends wire 21/s". YELLOW. Nails included. ITEM NO. SNUG-SWP-25 • (complete with nails) • 25 to counter pkg. • 20 pkgs. (500) to shipper • 21 lbs. ITEM NO. SNUG-SWP-25B SAME AS ABOVE - BLACK ITEM NO. SNUG-SRS-25 • (without nails) • 25 to pkg. • 20 pkgs. (500) to shipper • 16 lbs. ITEM NO. SNUG-SRS-25B SAME AS ABOVE - BLACK



Extends wire 21/8" from post. Pat. No. 4,599,488

WOODEX[®] 5WP/10 for wood posts. Extends wire 5 inches from post. Excellent for hogging down over old field fence. 3" of Woodex rests on 30d nail. Strong and sturdy. Molded of high density polyethylene with UV inhibitors. Complete with nails. Yellow. ITEM NO. WOODEX 5WP-10 • 10 to pkg • 25 pkgs • (250) to shipper • 22 lbs. ITEM NO. WOODEX 5WP-10B SAME AS ABOVE - BLACK



Extends wire 5" from post.

SNUG[®] **HT INSULATOR** for wood posts. Designed for high tensile use. Perfect for Equi-Rope and temporary fencing. Large diameter flange prevents arcing. Heavy fingers carry wire ³/₄" from post. Offered with galvanized ring shank nails or plain. Molded of high density polyethylene with carbon black for superior UV resistance. Performs in any climate.

ITEM NO. SNUG-HTN • (complete with galvanized ring shank nails) • 25 to counter pkg • 20 pkgs (500) to shipper • 26 lbs. • Black

ITEM NO. SNUG-HT • (without nails) • 25 to pkg • 20 pkgs (500) to shipper • 20 lbs. • Black

Premium line offering Life-Time Warranty. Pewter. ITEM NO. 2930-25 • 25 to pkg • 10 pkgs (250) to shipper • 14 lbs. • Pewter White available, see page 17.



Suitable for high tensile.

PINLOCK INSULATOR for wood posts. Heavy cross sections withstand the pressure of high tensile fencing. Attached pin easily locks and unlocks fence wire. Large flange prevents 'shorts' and arcing. Molded of high density polyethylene with carbon black for superior UV resistance.

Performs in any climate. Black.

ITEM NO. 2249-25 • (complete with galvanized ring shank nails) • 25 to pkg. • 20 pkgs (500) to shipper • 31 lbs.

ITEM NO. 2285-25 • (without nails) • 25 to pkg. • 20 pkgs (500) to shipper • 22 lbs. ITEM NO. 2285-25W SAME AS ABOVE - WHITE ITEM NO. 2285-25Y SAME AS ABOVE - YELLOW



Suitable for high tensile.

RING INSULATOR for corners, ends and line posts. Angled slot securely holds wire and rope up to 3/8". Black. *ITEM NO. 2671-25 • 25 to pkg. • 10 pkgs (250) to shipper • 15 lbs.*

White available, see page 18.

RING INSULATOR 6" EXTENDER screws into Wood Posts. Holds rope up to

8 MM,1/2" tape, and wire. White. ITEM NO. 2947-10 • 10 to pkg. • 20 pkgs (200) to shipper • 22 lbs.

RING INSULATOR POWER DRIVER Use with 110V or 12 Volt power drills.

Works with all Dare Ring Insulators. ITEM NO. 3003 • Individually packed • 5 to shipper • 2 lbs.

TUBE STYLE WOOD POST INSULATOR Rigid high density polyethylene with carbon black for superior UV resistance. Performs in any climate. Four inches long x 3/8" diameter. Ribs prevent insulator from sliding. Available with or without galvanized staples.

With 2" type III galvanized staple. *ITEM NO. 1724 • 50 to pkg • 10 pkgs (500) to shipper • 15 lbs.*

Insulator only - without staple ITEM NO. 1718 • 50 to pkg • 20 pkgs (1000) to shipper • 12 lbs.

PERMATEMP STAPLE INSULATOR for wood posts. Designed to be used with high tensile permanent electric fence or cameo monofilament line. Can be installed after wire is strung. Molded of highest quality polypropylene with carbon black for superior UV resistance. Performs in any climate. Type III galvanized 2" staple included.

ITEM NO. 1710 • 50 to pkg • 10 pkgs (500) to shipper • 13 lbs.









Suitable for high tensile.



Suitable for high tensile.

T - POST INSULATORS SNUG-STP-25 2934-25 SUPER SNUG® for T posts. Fits 1.25 & 1.33 lb/ft T posts. Large flange prevents arcing. Solid wire 1372-25 holders for electric fence wire, polywire and rope up to 8 mm. Snaps on and around post. Molded of high density polyethylene with UV inhibitors for all-weather performance. Yellow. ITEM NO. SNUG-STP-25 • 25 to pkg • 20 pkgs (500) to shipper • 22.5 lbs. ITEM NO. SNUG-STP-25W SAME AS ABOVE - WHITE (page 17) ITEM NO. SNUG-STP-25B SAME AS ABOVE - BLACK Premium line, offering life-time warranty. Pewter. ITEM NO. 2934-25 • 25 to pkg • 10 pkgs (250) to shipper • 11 lbs. SNUG JR. for small 1.0 lb./ft. T Posts ITEM NO. 1372-25 • 25 to pkg • 20 pkgs (500) to shipper • 13 lbs. STPX-25 T post insulator for Equi-Rope, coated wire, & large diameter fence materials up to 3/8". White. ITEM NO. STPX-25 • 25 to pkg • 20 pkgs (500) to shipper • 24 lbs. ITEM NO. STPX-25B SAME AS ABOVE - BLACK STPX-25 **EXTRA LENGTH SNUG**[®] for T POSTS. Extends wire 2¹/₂" from face of post... SNUG-XLSTP-25 otherwise same as STP. Yellow. ITEM NO. SNUG-XLSTP-25 • 25 to pkg • 10 pkgs (250) to shipper • 12 lbs. ITEM NO. SNUG-XLSTP-25B SAME AS ABOVE - BLACK Extends wire 2" from p EXTENDED LENGTH SNUG[®] for T POSTS. Extends wire 5" from face of post. SNUG-X5TP-25 Use to hog down sagging field fence...otherwise same as STP. Yellow ITEM NO. SNUG-X5TP-25 • 25 to pkg. • 10 pkgs (250) to shipper • 20 lbs. ITEM NO. SNUG-X5TP-25B SAME AS ABOVE - BLACK



Extends wire 5" from post

WESTERN[®] SCREW TIGHT for T Posts & sucker rods.

Adjusts to fit:

- T posts, steel small, medium & large, with or without studs.
- T posts, fiberalass medium & large sizes only.
- Sucker rods 3/4" diameter only.
- U posts small, 11/8" wide. Backside only.
- Small garden U posts-11/8" wide.

Insulator opens to attach anywhere on post.

ITEM NO. 2193-25 • 25 to pkg • 10 pkgs (250) to shipper • 19 lbs. ITEM NO. 2193-25B SAME AS ABOVE - BLACK

REVERSED T POST INSULATOR EXTENDER Holds wire 3" from backside

of T-Post. Snaps on and around post - insulator faces backward. ITEM NO. SNUG-RT-25 • 25 to pkg • 10 pkgs (250) to shipper • 17 lbs. ITEM NO. SNUG-RT-25B SAME AS ABOVE - BLACK



Adjusts to fit all T posts & 3/4" sucker rod Pat. No. 4, 845, 317



Pat. No. 4, 077.611

T POST TOP'R® SAFETY TOP AND ELECTRIC FENCE INSULATOR

Fits all T-Posts and can be nailed on top of wood posts. Protects horses and other valuable livestock from sharp, jagged T post tops. Large heavy-duty cap/insulator can be installed with wire holders facing front, back, right or left. Holds wire, polywire, polyrope and polytape up to 11/2". Molded of high density polyethylene with UV inhibitors for all weather performance. Yellow.

ITEM NO. 2027 • 10 to pkg • 10 pkgs (100) to shipper • 16 lbs. ITEM NO. 2027B SAME AS ABOVE - BLACK White available. See page 17, item no. 2929.

PINLOCK INSULATOR for T Posts. Fits 1.25 & 1.33 lb/ft posts. Heavy cross sections withstand the pressure of high tensile fencing. Large flange prevents 'shorts' and arcing. Molded of high density polyethylene with carbon black for superior UV resistance. Performs in any climate. Black.

ITEM NO. 2550-25 • 25 to pkg • 20 pkgs (500) to shipper • 23 lbs. ITEM NO. 2550-25W SAME AS ABOVE - WHITE ITEM NO. 2550-25Y SAME AS ABOVE - YELLOW



Fits all T posts Pat. No. 6,353,187



Suitable for high tensile


U - POST, CHAIN LINK, & SPECIALTY INSULATORS

SNUG[®] **INSULATORS** for U Posts & chain link fence. Holds wire 3³/₄" from post. Solid wire holders take smooth, barbed and polywire. Molded of high density polyethylene with UV stabilizer for all weather performance. Yellow.

Fits $1^{3}/_{4}$ " to $2^{1}/_{8}$ " wide posts.

ITEM NO. SNUG-SU-25 • 25 to pkg • 10 pkgs (250) to shipper • 14 lbs. ITEM NO. SNUG-SU-25 SAME AS ABOVE - BLACK

Fits 2³/₈" wide Steel City posts. Holds wire 1" from post. ITEM NO. XLSU-25 • 25 to pkg • 20 pkgs (500) to shipper • 20lbs.



GARDEN U-POST INSULATOR Fits all 1" to 1³/₈" U-posts. Ideal for gardens and light duty electric fencing. Holds wire 3/4" from post. Snaps on without tools. Yellow. *ITEM NO. SNUG-LGU-25 • 25 to pkg • 10 pkgs (500) to shipper • 8 lbs.*



U POST TOP'R® SAFETY TOP AND ELECTRIC FENCE

INSULATOR. Fits $1^{3}/_{*}$ and $2^{1}/_{*}$ wide full weight U posts. Protects horses and other valuable livestock from sharp post tops. Large, heavy-duty cap/insulator can be installed with wire holders facing front or back. Holds wire, polywire, polyrope and polytape up to $1^{1}/_{*}$. Molded of high density polyethylene with UV inhibitors for all weather performance. Yellow.

ITEM NO. 2087 • 10 to pkg • 10 pkgs (100) to shipper • 15 lbs. ITEM NO. 2087W SAME AS ABOVE - WHITE ITEM NO. 2087B SAME AS ABOVE - BLACK



INSULATOR FOR CHAIN LINK POSTS, TOP RAIL, TUBE GATES & CORRAL PANELS

Fits vertical or horizontal tubes/pipes up to 2" round or square. Holds rigid wire up to 5/16" and pliable ropes up to 3/8". Extends wire 3.5" from post. Heavy duty 1/4" hardware included. (Can be fastened to almost anything). Black.

ITEM NO. 3359-10 • 10 to pkg • 10 pkgs (100) to shipper • 18 lbs.







Pat. No. D 594,821 S

TRADITIONAL STYLE INSULATORS

ELFIN® ELECTRIC FENCE INSULATOR for wood posts. Weather resistant black polyethylene performs in any climate. One wire holder takes any standard fence wire. Metal wire holding clip not required. Black only. ELFIN® WITH NAIL FOR WOOD POSTS ITEM NO. ELF-WP-25 • 25 to pkg • 20 pkgs (500) to shipper • 15 lbs.

ELFIN® INSULATOR ONLY ITEM NO. ELF-RS-25 • 25 to pkg • 20 pkgs (500) to shipper • 10 lbs.

ELFIN® WITH ESSEX BRACKET for T Post. U Post & chain link fence. Extends

wire five inches from fence. Fits either side of chain link, studded T & U posts. Consists of heavy steel bracket with Elfin® insulator, screw, and cotter pin. All metal parts plated to resist rust. ITEM NO. 1362-10 • 10 to counter pkg • 10 pkgs (100) to shipper • 16 lbs.





DARE BLACK WIDOW™ ELECTRIC FENCE INSULATOR

High density black linear polyethylene with UV inhibitors. Operates well in any climate, in any part of the world. 45 degree slot easily accepts any fence wire and holds it in place. BLACK WIDOW™...a very good insulator. Black only.

BLACK WIDOW™ WITH NAIL FOR WOOD POSTS ITEM NO. BW-WP-25 • 25 to pkg • 20 pkgs (500) to shipper • 15 lbs.

BLACK WIDOW™ INSULATOR ONLY ITEM NO. BW-RS-25 • 25 to pkg • 20 pkgs (500) to shipper • 10 lbs.



BW-WP-25 BW-RS-25

PORCELAIN AND PORCELAIN STYLE INSULATORS

TRIPLE GROOVE LINE INSULATORS

Old-fashioned style insulators molded of modern high density polyethylene. Smooth and glossy like porcelain. Takes any size fence wire. Install like any insulators. Will not crack or shatter if struck with hammer. White.

ITEM NO. TGN-25 • insulators with nails • 25 to pkg • 20 pkgs (500) to shipper • 20 lbs. Use 458 clip to secure wire to insulator (page 13).

PORCELAIN LINE INSULATORS Produced from specially formulated electrical porcelain for superior dielectric and mechanical strength. Imported.

Standard size porcelain line insulator with 10d double headed nail and poly washer. *ITEM NO. 16D-25 • 25 to pkg • 20 pkgs (500) to shipper • 49 lbs.*

Standard size porcelain line insulator. No fittings or nails. ITEM NO. 16-25 • 25 to pkg • 20 pkgs (500) to shipper • 44 lbs.

Small porcelain lag insulator. Use for line and corners. ITEM NO. 2802-25 • 25 to pkg • 4 pkgs (100) to shipper • 23 lbs.

Large porcelain lag insulator. Heavy duty. Use for line and corners. *ITEM NO.* 2799-25 • 25 to pkg. • 2 pkgs (50) to shipper • 29 lbs.

Heavy duty porcelain corner insulator. No. 36 ITEM NO. 2356-10 • 10 to pkg. • 25pkgs (250) to shipper • 48 lbs.

Large porcelain lag insulator. Heavy duty. Use for line and corners. ITEM NO. 1629-10 • 10 to pkg. • 10 pkgs (100) to shipper • 24 lbs.













CORNER INSULATORS

ROUNDER™ CORNER White polyethylene corner knob. Looks like porcelain. Weighs less. Works great. White only. *ITEM NO. 1388-10 • 10 to pkg • 25 pkgs (250) to shipper • 8 lbs.*



CORNER POST INSULATOR Insulator opens and latches closed for ease of fence installation. Molded of high density polyethylene with carbon black for superior UV resistance. Performs in any climate. Black only. *ITEM NO. BW-CP-10 • 10 to pkg • 25 pkgs (250) to shipper • 6 lbs.*

CORNER KNOB INSULATOR Large flanges. Heavy center section. Large enough to withstand strain of fence wire and offer complete insulation. Flexible tabs speed installation. Not recommended for high tensile. Molded of high density polyethylene with carbon black for superior UV resistance. Performs in any climate. Black only.

ITEM NO. BW-KK-10 • 10 to pkg • 25 pkgs (250) to shipper • 7 lbs.





12

'CLIPPER' Wire to insulator fastening clip. Handy spring clip for fastening electric fence wire to grooved insulators. Galvanized spring wire. ITEM NO. 458 • 100 to pkg • 10 pkgs (1000) to shipper • 5 lbs.

TUBULAR CORNER POST & END POST INSULATOR

Provides insulation for 90° turn or end loop on any style post. Flat-sided design resists rolling and speeds installation. Heavy sidewalls provide extra protection against 'shorts' or 'grounds'. Molded of polyethylene with carbon black to withstand the elements. Molded with metal insert designed to take high-tensile strain. 191/2" long.

ITEM NO. 1779 • 10 to pkg • 10 pkgs (100) to shipper • 16 lbs. Custom lengths and bulk coils available on request.

HIGH STRAIN CORNER & END ASSEMBLY Performs superbly from any wood post or tree - as a corner - for straight line fencing. Consists of 3/8" diameter hi-carbon steel bracket, 1752 insulator and self-locking nut. Wire clip may be required when used for straight line fencing. All metal parts zinc plated.

ITEM NO. 451 • 10 assemblies to pkg • 5 pkgs (50) to shipper • 16 lbs.

FASTENERS & CLIPS

ITEM NO. 457 • 100 to pkg • 10 pkgs (1000) to shipper • 14 lbs.

'TWISTER' Wire insulating mounting fastener. Low-cost insulator-to-post fastener.

For use on Angle, 'T', or Channel 'U' posts. Galvanized wire. A favorite on the Gayle farm in Kansas.

"EGG" STYLE CORNER AND END INSULATOR

ITEM NO. 2949-10 • 10 to pkg • 10 pkgs (100) to shipper • 8 lbs.

All weather black.

Glass reinforced polyester. Strongest Dare corner. Suitable for high tensile and Rope to 1/4".

ITEM NO. 2210-10 • 10 to pkg • 20 pkgs (200) to shipper • 12 lbs.

sections to withstand the pull of high tensile wire. Molded of an engineering grade polymer.

2210-10 Suitable for high tensile 2949-10

HIGH STRAIN CORNER AND END INSULATOR Molded of high

strength engineering grade polymer. Able to withstand the constant pressure of high tensile fence wire. Use for corners, ends, dips and rises. All weather black only. ITEM NO. 1752-10 • 10 to pkg • 25 pkgs (250) to shipper • 12 lbs.

DOUBLE U END AND CORNER INSULATOR Designed with heavy cross

451 Suitable for high tensile and Equi-Rope













STUDDED 'T' POST FASTENING CLIPS for 1.25 & 1.33 LB/FT standard

size STUDDED T POSTS. Not for electric fence. Heavily galvanized 11 gauge wire. Use to fasten fence or barbed wire to posts.

ITEM NO. 440 • 25 to pkg • 40 pkgs (1000) to shipper • 19 lbs.

CLIP FOR WOOD AND POLY BATTENS Fits all sizes up to 2"x2". Use fo fasten high tensile, ordinary electric, non-electric, smooth or barbed fence wire to treated wood and poly battens. 12¹/₂ gauge type III galvanized wire. ITEM NO. 1699 • 100 to pkg • 10 pkgs (1000) to shipper • 15 lbs.

ROUND POST FASTENER Cotter pin style. Use to fasten high tensile wire to drilled 1¹/₄" - 1¹/₂" fiberglass rods. 13 gauge type III galvanized wire.

ITEM NO. 2529 • 100 to pkg • 10 pkgs (1000) to shipper • 22 lbs.

ELECTRIC FENCE POSTS

STEP-IN POLY POST Ideal for temporary electric fencing such as controlled grazing/pasture management. Lightweight, self-insulating, and convenient to use. Strong H section post molded of UV resistant polypropylene. Eight wire holders for steel wire, poly wire and poly tape up to $11/2^{"}$ wide. Spaced 6" to 37" from ground up. Sharp metal spike end of post easily stepped into hard ground. Specifications: 48" long. Packed 50 to retail store display carton. Can be shipped via UPS. Individually bar-coded. Specify black, white, yellow or orange. *ITEM NO. 2400, 2400W, 2400Y, 2400O • 50 to carton • 39 lbs.*

63" STEP-IN POLY POST Molded of UV resistant polyolefin reinforced with glass-fiber. 8 holders for wire/tape/rope. 63" length—54" above ground. White. *ITEM NO. 2600W* • 30 to carton • 28 lbs.

DARE WESTERN® / SET-EZE® POST

A natural combination. Western[®] Screw Tight Insulators and Posts. Wrap around anchor plate, cold drawn steel rod. 20 posts to carton.

| Specifications | ltem Number | Description | Wt. Per 100 |
|--|----------------|-----------------------------------|-------------|
| 23/64" dia. steel rod. Wrap around anchor plate. | 62-2W-54 | Post with 2 Western Insulators | 143 lbs. |
| 20 posts to carton. With insulators as noted. | 62-1W-54 | Post with 1 Western Insulator | 138 lbs. |

SET-EZE® ADJUSTABLE STEEL POSTS BUNDLED - NOT BOXED

| Specifications | ltem Number | Description | Wt. Per 100 |
|---|----------------|-------------|-------------|
| 5/16" dia. steel rod. Wrap around anchor plate. 25 posts to bundle. | 1552-48 | Post Only | 113 lbs. |













ALUMINUM ELECTRIC FENCE WIRE

Aluminum electric fence wire is four times more conductive than galvanized steel and more visible. Lightweight and easy to install. Guaranteed against rust. Do not use with a weed burner style of charger. Recommended for use with a low impedance type energizer.

14 ga x 1/4 mile aluminum wire on plastic spool ITEM NO. 14AL1320 • 4 to carton/shipper • 31 lbs.

14 ga x 1/2 mile aluminum wire on plastic spool ITEM NO. 14AL2640 • 4 to carton/shipper • 59 lbs.

16 ga x 164 ft aluminum wire on plastic spool *ITEM NO. 16AL164 • 16 to carton/shipper • 12 lbs.*

16 ga x 1/4 mile aluminum wire on plastic spool *ITEM NO. 16AL1320 • 4 to carton/shipper • 20 lbs.*

16 ga x 1/2 mile aluminum wire on plastic spool *ITEM NO. 16AL2640 • 4 to carton/shipper • 40 lbs.*

EQUINE PRODUCTS

EQUINE POLYROPE

7MM POLY EQUI-ROPE X 656 FT. Premium braided HDPE& polyester mix rope with 12 strands of stainless steel wire. 9/32³⁰⁹ approx. diameter. White 1,592 lbs .average breaking strength. *ITEM NO. 3097 • 2 rolls per carton • carton weight 25 lbs.*

6MM POLY EQUI-ROPE X 600 FT. Braided HD Dacron rope with 7 strands of stainless steel wire. 1/4" approx. diameter. Approx. 820 lbs. average breaking strength. WHITE. ITEM NO. 3094 • 2 rolls per carton • carton weight 14 lbs. ITEM NO. 3094 § (Same as 3094, but black rope with white tracers—high visibility for horses)

4MM POLY EQUI-ROPE X 656 FT. Braided HD polyethylene rope with 3 strands of stainless steel wire. 5/32" approx. diameter. 492 lbs. average breaking strength. WHITE. *ITEM NO. 3095 • 4 rolls per carton • carton weight 16 lbs.*

6MM POLY TWISTED ROPE X 600 FT. Twisted HD polyethylene rope with 7 strands of stainless steel wire. 15/64" approx. diameter. 720 lbs. approximate tensile strength. WHITE. *ITEM NO.* 3365 • 2 rolls per carton • carton weight 17 lbs.

EQUINE POLYTAPE & POLYWIRE

Highly visible, lightweight and easy to use. A combination of weather resistant polyethylene and strong stainless steel wire conductors.

POLYTAPE Woven of white UV resistant polyethylene and stainless conductor wires. Available in two widths. 1/2" wide with five conductors and 1¹/₂" with fifteen conductors. Install with tape insulators only. 3 to 4 twists recommended between posts to prevent whipping from wind. *ITEM NO.* 2327 • 1/2" wide x 200 meters/656 ft. • 6 to ctn • 17 lbs. *ITEM NO.* 2346 • 1/2" wide x 400 meters/1312 ft. • 6 to ctn • 29 lbs.

ITEM NO. 2576 • 1-1/2" wide x 200 meters/656 ft. • 6 to ctn • 23 lbs.

Heavy Duty—50% heavier strands of stainless steel. ITEM NO. 3171 • White • 1-1/2" wide x 200 meters/656 ft. • 2 to ctn • 15 lbs. ITEM NO. 3171B • Black • 1-1/2" wide x 200 meters/656 ft. • 2 to ctn • 15 lbs.

POLYWIRE White polyethylene cord woven of UV resistant polyethylene with three strands of strong stainless steel wire. Available in two lengths. Individually shrink wrapped. *ITEM NO.* 2343 • 250 meters / 820 ft • 10 to ctn • 19 lbs. *ITEM NO.* 2347 • 400 meters/1312 ft. • 6 to ctn • 17 lbs.

Heavy Duty—same as above with 6 strands of stainless steel. ITEM NO. 3174 • 200 meters/656 ft. • 6 to ctn • 12 lbs. ITEM NO. 3420 Ranch Hand See Page 18 ITEM NO. 3177 • 400 meters/1312 ft. • 6 to ctn • 22 lbs.



2346



2343 3174 2347 3177



3094-Braided 3365-Twisted



3094B



2576-Standard 3171-Heavy Duty



3171B-Heavy Duty

14

EQUINE INSULATORS

For any polytape up to 11/2" wide. Insulators grip tape tightly to prevent whipping and sawing. Heavy tape holder unlocks to aid installation. Molded of all-weather high density polyethylene.

WOOD POST INSULATOR for tape. Complete with nails. ITEM NO. 2330-25 (yellow) • 25 to pkg • 10 pkgs to shipper • 15 lbs. ITEM NO. 2330-25W SAME AS ABOVE - WHITE ITEM NO. 2330-25B SAME AS ABOVE - BLACK

WOOD POST TAPE INSULATOR EXTENDER For polytape up to 11/2" wide. Extends tape 31/2" from post. Nails included. ITEM NO. 2338-25 (yellow) • 25 to pkg • 10 pkgs to shipper • 18 lbs.

TEM NO. 2338-25W SAME AS ABOVE - WHITE ITEM NO. 2338-25B SAME AS ABOVE - BLACK

Pat no. 6,353,137

2330-25

2338-25

SNUG-HTW



2330-25W



WOOD POST OR VINYL POST INSULATOR

For polywire, polyrope or high tensile wire. Use two galvanized roofing nails or two #8 x 3/4" stainless screws (not included). Equine white. *ITEM NO. SNUG-HTW* • 25 to pkg • 20 pkgs (500) to shipper • 17 lbs.

RING INSULATORS Ring insulators for line, end, and corner posts. Holds electric wire and rope up to 8mm. ITEM NO. 2671W (white) • 10 to pkg • 20 pkgs (200) to shipper • 11 lbs. ITEM NO. 2671-25 (black) • 25 to pkg • 10 pkgs (250) to shipper • 15 lbs.





RING INSULATORS 6" EXTENDER for wood posts.

Holds wire, rope up to 8MM and 1/2" tape. ITEM NO. 2947-10 • 10 to pkg • 6 pkgs (120) to shipper • 13 lbs.



RING INSULATOR POWER DRIVER

Use with 110V or 12 Volt power drills. Works with all Dare Ring Insulators. *ITEM NO. 3003 • Individually packed • 5 to shipper • 2 lbs.*



EQUINE INSULATORS

EQUI-ROPE CORNER POST BRACKET KIT

Each consists of: one plated steel bracket, one #1388 insulator and one 1/4-20 locking nut. ITEM NO. 3283 • 4 to pkg • 6 pkgs to shipper • 7.5 lbs.



T-POST INSULATOR for polytape up to 11/2" wide. Now holds rope and polywire. Fits 1.25 & 1.33 lb./ft T posts. ITEM NO. 2334-25 (yellow) • 25 to pkg • 10 pkgs (250) to shipper • 12 lbs. TEM NO. 2334-25W SAME AS ABOVE - WHITE ITEM NO. 2334-25B SAME AS ABOVE - BLACK





Pat no. 6,353,137

T-POST TAPE INSULATOR EXTENDER

Extends wire 31/2" from post. Fits 1.25 and 1.33 lb/ft T-post. For polytape up to 11/2" wide. ITEM NO. 2340-25 (yellow) • 25 to pkg • 10 pkgs (250) to shipper • 17 lbs. ITEM NO. 2340-25W SAME AS ABOVE - WHITE






Pat. no. 6.353.137

STPX-25 T post insulator for Equi-Rope, coated wire, & large diameter fence materials up to 3/8". White. ITEM NO. STPX-25 • 25 to pkg • 20 pkgs (500) to shipper • 24 lbs. ITEM NO. STPX-25B SAME AS ABOVE - BLACK



T-POST SAFETY TOP-R


Fits all T-Posts and can be nailed on top of wood post. For all wire, polywire, polyrope and tape up to $1^{1/2}$ ". Will face all directions on post. Equine white. ITEM NO. 2929 • 10 to pkg • 10 pkgs (100) to shipper • 17 lbs.





ROUND POST INSULATOR for tape up to 1¹/₂" wide.

Fits 1/4" to 9/16" dia. posts. ITEM NO. 2336-25 (yellow) • 25 to pkg • 10 pkgs (250) to shipper • 13 lbs. ITEM NO. 2336-25W SAME AS ABOVE - WHITE





EQUINE INSULATORS

LARGE WESTERN® FOR SUCKER RODS and other oversized round posts. Fits 1/4" to 7/8" dia and 5/8" fiberglass T-posts. Holds all wire, polywire, polyrope and polytape up to 11/2". Yellow. ITEM NO. XLRP-25 (yellow) • 25 to pkg • 10 pkgs (250) to shipper • 17 lbs. ITEM NO. XLRP-25W SAME AS ABOVE - WHITE ITEM NO. XLRP-25B SAME AS ABOVE - BLACK





U POST INSULATOR for polytape up to 11/2" wide. Fits 13/4" to 21/6" wide posts. ITEM NO. 2332-25 (yellow) • 25 to pkg • 10 pkgs (250) to shipper • 11 lbs. ITEM NO. 2332-25W SAME AS ABOVE - WHITE ITEM NO. 2332-25B SAME AS ABOVE - BLACK

U POST TOP'R for tape. Holds all wire, polywire, polyrope and polytape up to 1½". *ITEM NO. 2087 (yellow)* • 10 to pkg • 10 pkgs (100) to shipper • 15 lbs. *ITEM NO. 2087-25W* SAME AS ABOVE - WHITE *ITEM NO. 2087-25B* SAME AS ABOVE - BLACK






POLYTAPE AND POLYWIRE ACCESSORIES

T-POST VINYL SAFETY CAP Provides attractive top to T-Post fence line while protecting livestock from jagged tops. Highly visible white. *ITEM NO. 2927-25 • 25 to pkg • 10 pkgs (250) to shipper • 12 lbs.*



TAPE ELECTRICAL CONNECTOR for tape up to 1¹/₂". Use to connect fence charger to tape or as an end clamp. May be used to fasten 1/2" tape to a gate handle. *ITEM NO. 2743 • 2 connectors to counter pkg • 10 pkgs (20 connectors) to shipper • 3 lbs.*






TAPE BUCKLE / GATE ANCHOR for tape up to 1/2" polytape.

Use to splice two lengths of tape. Attach to pinlock insulator to form gate anchor or tape end. Has many uses.

ITEM NO. 2768 • 5 buckles to pkg • 10 pkgs (50 buckles) to shipper • 2 lbs.

Tape buckle for 11/2" tape. ITEM NO. 2880 • 2 buckles to pkg • 10 pkgs (20) to shipper • 2 lbs.





POLYTAPE & POLYWIRE ACCESSORIES

CORNER AND END TENSIONERS for 1¹/₂" polytape installed on wood or T-posts. Use at corners, ends or T junctions. Fully insulated. All metal parts are of #300 series stainless steel. Insulators are molded of white high density polyethylene with UV inhibitors. Each assembly includes an electrical connector consisting of one self tapping lag screw and one wire terminal. Use to connect to energizer or jumper as well. ITEM NO. 4023 3-way Tensioner • 1 to pkg • 10 pkgs to shipper • 4 lbs. ITEM NO. 2810 Corner Tensioner • 2 to pkg • 10 pkgs to shipper • 4 lbs. ITEM NO. 3245-A Tape Clip for 11/2" Tape • 25 to pkg • 10 pkgs to shipper • 2.5 lbs. ITEM NO. 2809 End Tensioner • 2 to pkg • 10 pkgs to shipper • 3 lbs. ITEM NO. 3115 Corner and End Tensioner for 1.25/1.33 T-posts • 1 to pkg 10 pkgs to shipper • 3 lbs.

GATE KIT for 11/2" polytape. Consists of 2 #2810 tensioner/anchors and one #4024 gate handle. ITEM NO. 4002 • 1 kit to pkg • 10 pkgs (10 kits) to shipper • 8 lbs. ITEM NO. 4024 Gate Handle with 11/2" tape tensioner • 1 to pkg • 20 pkgs to shipper • 6 lbs. ITEM NO. 1247W White Gate Handle only • 10 gates to pkg • 5 pkgs (50) to shipper • 15 lbs.

IN-LINE TENSIONER Use with Equi-Rope and electric fence wire gauges 14 thru 18. Molded of engineering grade polymer. Imported. ITEM NO. 2341 • 1 to pkg • 20 to shipper • 6 lbs.

HANDLE for 2341 In-Line Tensioner. ITEM NO. 2770 • 5 to shipper • 10 lbs.

WIRE TIGHTENER Use with polywire, 1/2" polytape, and steel wire gauges 14 thru 18. Not designed for high tensile. ITEM NO. 2769 • 5 to counter pkg • 4 pkgs (20) to shipper • 3 lbs.

E-Z'REEL large winder & spool. Equipped with neck strap & fence hooks to hang. Holds 500' Equi-rope & 11/2" polytape; 1/4 mile of 1/2" polytape and 1 mile polywire. ITEM NO. 3199 • 2 to shipper • 10 lbs.

EMPTY SPOOL Replacement spool or extra for #3199. Same capacity as above. ITEM NO. 3200 • 4 to shipper • 10 lbs.





3200










4002

234







4024

POLYTAPE & POLYWIRE ACCESSORIES

TAPE AND WIRE WINDER Use to recover electric fence wire, polywire or polytape. Complete with spool. Capacity—22 lbs. of steel wire or 400 meters (1/4 mile) of polywire. *ITEM NO. WW-1 • 6 to shipper • 9 lbs. ITEM NO. EFS-1 (extra spools) • 10 to shipper • 5 lbs.*

ELECTRIC ROPE CLAMP Use to splice or end polyrope 1/4" to 5/16" in diameter. Also use to connect hot wire from energizer. New collar eases installation—acts as extra helping hand. *ITEM NO. 3098 • 4 to pkg • 10 pkgs (40) to shipper • 4 lbs.*

HIGH TENSILE FENCE SUPPLIES

WIRE STRAINER/TIGHTENER Install in fence line to periodically renew tension. Heavy cast cog with spring loaded latch. Hot dip zinc coated frame exceeds type III specifications. No raw uncoated steel edges. Use no. 1701 handle to tighten. ITEM NO. 1703 • 20 strainers to shipper • 11 lbs.

WIRE STRAINER/TIGHTENER Tighten with 9/16" crescent or open end wrench or 1701 handle. ITEM NO. 1703C • 50 strainers to shipper • 20 lbs.

STRAINER HANDLE Use to tighten strainers no. 1703 & 1703C. Tension measuring scale on handle. Heavy riveted construction. Zinc plated. *ITEM NO. 1701 • 5 to shipper • 5 lbs.*

NO-CUT WIRE STRAINER Use to tighten high tensile and other smooth fence wire. Die-cast zinc. Tighten with #2776 or 1/2" drive socket handle. *ITEM NO. 2775 • 20 to shipper • 5 lbs.*

TIGHTENER HANDLE Use with #2775 ITEM NO. 2776 • 5 to shipper • 10 lbs.











3098

1703

HIGH TENSILE FENCE SUPPLIES

TENSION MEASURING SPRING Install in each fence line together with strainer. Necessary to keep wires taut during temperature changes. Use to determine tension on wires. All parts are hot dip galvanized and exceed type III specifications. ITEM NO. 1713 • 20 to shipper • 30 lbs.

GALVANIZED BARBED FENCE STAPLES Slash-cut style staple with barbs. Heavy .148" diameter by length shown. Type III zinc coating for long life. Suitable for high tensile and all other types of fence installations.

ITEM NO. 1692 • 50 staples to counter pkg • 20 pkgs (1000) to shipper • 21 lbs. 1-7/8" staple

1-7/8" staple

ITEM NO. 2415 • 10 lbs. to counter pkg • 4 pkgs (40 lbs) to shipper • 43 lbs.

BRACE PINS Use to hold horizontal wood brace beams. 3/8" dia. x 5" & 10". Galvanized steel. 10 in pin ITEM NO. 1714 - 5 • 5 to counter pkg • 10 pkgs (50) to shipper • 15 lbs. 5 in. pin ITEM NO. 1715 - 5 • 5 to counter pkg • 10 pkgs (50) to shipper • 8 lbs.

POLY BATTEN Use as wire spacer between line posts. Place every 25 ft. or as needed. Battens float above ground. 11/2" wide x 1" deep x 49". Notched every inch. High density polyethylene with carbon black UV inhibitor. Black. Use with clip no. 1699. See page 13. ITEM NO. 2490 • 25 to bundle • 18 lbs.

UNDERGROUND EARTH ANCHOR Use wherever an earth anchor is needed. 3/16" x 54" cable attached for easy installation. Drive 24 to 30 inches into the ground. Pull up to set, 1100 lb, holding power in average soil.

ITEM NO. 2208 • 1 to counter pkg • 5 pkgs to shipper • 2.2 lbs. DUCKBILL DRIVING ROD. Use to drive no. 2208. 1/2" dia x 36" steel. ITEM NO. 2217 • 1 to shipper • 3 lbs.

WIRE DEREELER/SPINNING JENNY. Knock-down style. Equipped with brake pad to prevent overrunning. Use to spin off coils of high tensile or ordinary fence wire. Accomodates any common weight fence wire coil. Adjusts to fit 17" to 23" I.D. coil. Packaged to display on retail counter. Ships UPS. ITEM NO. 2420 • 1 to counter pkg • 5 to shipper • 60 lbs.

WIRE DEREELER/SPINNING JENNY - PROFESSIONAL MODEL


Equipped with fully adjustable brake to prevent overrunning. Large angle iron base permits truck bed mounting. Accomodates any common weight fence wire coil. Adjusts to fit 17" to 23" I.D. coils. Some assembly required.

ITEM NO. 2577 • 1 to shipper • 21 lbs.



STERIO COCOCOLUTE











HIGH TENSILE FENCE SUPPLIES

WIRE TWISTING TOOL Use to spin, bend, splice & dice high tensile wire. Also use to bend T Post and batten clips. 7/16" dia x 5" zinc plated steel tool. Drilled three holes. (Will not chop) ITEM NO. 1707 - S • 1 to counter pkg • 10 pkgs to shipper • 3 lbs.



| WIRE CUTTER Specially hardened jaws designed to cut 12 ¹ / ₂ ga. high tensile wire. Pocket size - 9" overall length. Imported. ITEM NO. 2290 • 1 to counter pkg • 5 to shipper • 5 lbs. | 2290 |
|---|------|
| | |

 ROUND NOSE PLIERS for general use, fence installation & repair. Will not cut high tensile
 2999

 wire. Imported.
 ITEM NO. 2999 • Individually labeled • 5 to shipper • 6 lbs.

FENCE TOOL for general use. Corrugated hammerhead, two wire cutters & staple puller. Large 10¹/₂" overall length. Will not cut high tensile wire. Individually carded. Imported. *ITEM NO. 3001 • 5 to shipper • 8 lbs.*

CHAIN GRAB PULLER for the professional installer. Use to stretch and splice fence wire. Smooth jaws for minimal wire marking. Imported. *ITEM NO. 2456 • 1 to shipper • 7 lbs.*

FENCE POST BRACKETS Build 'H' braces without drilling. Use two nailing brackets per horizontal. 16 gauge galvanized steel. Individually labeled.

SMALL. Use to attach 2" - 4" dia. horizontals to 31/2" - 5" dia. posts. *ITEM NO. 2965 • 8 to counter pkg • 6 to shipper • 6 lbs.* LARGE. Use to attach 4" - 6" dia. horizontals to 5" - 8" dia. posts. *ITEM NO. 2966 • Bulk • 50 to shipper • 13 lbs.*





<u>SPLICING EQUIPMENT</u>

DARE SLEEVES, TAPS AND TOOLS The sleeves and taps are designed to speed and improve installation and repair of all common sizes of barb, woven and smooth fence wire. DARE SPLICING SLEEVES equal and often exceed the breaking strength of the original wire. They are the only style recommended by most manufacturers of high-tensile systems. DARE TAPS are handy when used to connect hook-up, grounding and jumper wires to the fence line. Trouble-free connections can be made quickly and easily. Special application tools are made of high-carbon tool steel and are provided with gauges to insure strong and dependable splices and connections.

SPLICING SLEEVES

Use to splice 14¹/₂ & 15¹/₂ gauge smooth wire. ITEM NO. DP 1-2/25 • 25 to counter pkg • 20 pkgs (500) to shipper • 1.6 lbs. ITEM NO. DP 1-2/100 • 100 to counter pkg • .3 lbs. • no standard shipper

Use to splice $12^{1/2}$ gauge smooth wire.

ITEM NO. DP 2-3/25 • 25 to counter pkg • 20 pkgs (500) to shipper • 2.9 lbs. ITEM NO. DP 2-3/100 • 100 to counter pkg • .5 lbs. • no standard shipper ITEM NO. DP 2-3/500 • 500 to counter pkg • 3 lbs. • no standard shipper Extra length splicing sleeves. Use in place of two #DP 2-3 sleeves. For 12¹/₂ ga. ITEM NO. XL 2-3/100 • 100 to counter pkg • 1.0 lb. • no standard shipper

Use to splice 10 & 11 ga. smooth and 14 & $15^{1\!/_2}$ ga. barbed wire.

ITEM NO. DP 3-4/10 • 10 to counter pkg • 20 pkgs (200) to shipper • 3.5 lbs. ITEM NO. DP 3-4/100 • 100 to counter pkg • 1.6 lbs. • no standard shipper Use to splice 9 ga. smooth, 12¹/₂ & 13¹/₂ ga. barbed wire.

ITEM NO. DP 4-5/10 • 10 to counter pkg • 20 pkgs (200) to shipper • 4.7 lbs. ITEM NO. DP 4-5/100 • 100 to counter pkg • 2.2 lbs. • no standard shipper

Use to splice 7 ga. smooth wire. *ITEM NO. DP 5-6/100* • 100 to counter pkg • 5 lbs. • no standard shipper* *Special #2878 crimping tool needed



FENCE TAPS

Connect $12^{1}/2-14^{1}/2$ ga. smooth wire & $15^{1}/2$ ga. barbed wire to $12^{1}/2-16$ ga. smooth hook-up wire. *ITEM NO. DPT 3-4/10 • 10 to counter pkg • 20 pkgs (200) to shipper • 1.2 lbs. ITEM NO. DPT 3-4/100 • 100 to counter pkg • .5 lb. • no standard shipper*

CRIMPING TOOLS FOR SLEEVES & TAPS

Four slot hand tool to press sleeves and taps above, except DP 5-6. Our best selling tool. Imported. 21" overall. *ITEM NO.* 2154 • 1 to counter pkg • 5 to shipper • 32 lbs.

Two slot hand tool to press sleeve DP 2-3 and fence tap DPT 3-4 only. 12"overall. Small compact size makes your fencing chore a snap. *ITEM NO. 2132 • 1 to carton • 5 to shipper • 15 lbs*







WIRELINK* In-line style wire splicer. Use to splice high tensile and other fence wires. Embossed jaws grip firmly. No tools required.

Use to splice $12^{1/2} / 16$ ga (.099" /.062") wire - best for high tensile. ITEM NO. 2081 (5057) • 100 to shipper • 3 lbs.

Use to splice 11¹/₂ / 12¹/₄ ga (.113" / .102") wire ITEM NO. 2108 (5059) • 100 to shipper • 4 lbs.

Use to splice 10 / 11 ga (.135" / .120") wire ITEM NO. 2114 (5063) • 100 to shipper • 7 lbs.

Use to splice Cameo, Bayco and 8-9 ga (.163" / .148") wire ITEM NO. 2545 (5065) • 100 to shipper • 7 lbs.

*Wirelink is a trademark of Reliable Power Products, Inc.

WIREVISE⁺ A 'no knot' method to secure high tensile fence wire to end posts. Embossed jaws grip firmly. Pull tested to meet or exceed breaking strength of high tensile fence wire.

Use for $12^{1/2}$ to 16 ga (.099"-.062") wire. Best for high tensile. ITEM NO. 2080 (5056) • 100 to shipper • 3 lbs. Use for 111/2 to 121/4 ga (.113" / .102") wire ITEM NO. 2112 (5058) • 100 to shipper • 4 lbs. Use for 10 to 11 ga (.135" / .120") wire ITEM NO. 2113 • (5062) • 100 to shipper • 4 lbs. Use for Cameo, Bayco and 8-9 ga (.163" / .148") wire ITEM NO. 2544 (5064) • 100 to shipper • 4 lbs.

*Wirevise is a trademark of Reliable Power Products, Inc.

SPLIT BOLT/LINE TAP Die cast zinc split bolt and washer with galvanized steel nut provide trouble-free connections. Use to connect hook-up or grounding wire to fence. Not a splice. ITEM NO. 2083 • 10 to counter pkg • 10 pkgs (100) to shipper • 8 lbs.

DARE LINE CLAMP/TAP Split bolt style. 3-pack. ITEM NO. 2083-3 • 3 to counter pkg • 10 pkgs (100) to shipper • 2.5 lbs.

KWIK SPLICE[™] Quick, easy and economical splices for fence wire, smooth & barbed. Splicing tool #3075 required.

Stainless steel splice for 121/2-151/2 ga (.099"-.067") high tensile smooth & woven wire. ITEM NO. 3070 KWIK SPLICE SLEEVE • 50 to pkg • 6 pkgs (300) to shipper • 5 lbs. Galvanized steel splice for 121/2-14 ga barbed & 9 ga (.148") smooth wire. ITEM NO. 3071 KWIK SPLICE SLEEVE • 50 to pkg • 6 pkgs (300) to shipper • 4 lbs.

Galvanized steel wire for 10-16 ga (.135"-.062") smooth & woven wire. ITEM NO. 3072 KWIK SPLICE SLEEVE • 50 to pkg • 6 pkgs (300) to shipper • 4 lbs. Galvanized steel splice for 121/2-151/2 (.099"-.067") smooth & woven high tensile wire.

ITEM NO. 3073 KWIK SPLICE SLEEVE • 50 to pkg • 6 pkgs (300) to shipper • 4 lbs. Galvanized steel wire for 151/2 ga high tensile barbed wire.

ITEM NO. 3080 KWIK SPLICE SLEEVE • 50 to pkg • 6 pkgs (300) to shipper • 5 lbs.

KWIK SPLICE[™] CRIMPING TOOL Use to attach/crimp KWIK SPLICE[™].

Cuts high tensile wire. 18" overall. ITEM NO. 3075 KWIK SPLICE TOOL • 1 to carton/shipper • 6.4 lbs.



2083





2080, 2112, 2113, 2544







Gripple Plus Wire Joiners & Tensioners range for use in fencing, trellising, and greenhouse applications.
Suitable for all types and sizes of wire (mild or high tensile steel, and polymer wire too)
Use on plain, barbed, or electric wire and on all types of stock fence • Adjustable and re-tensionable
Ideal for use at installation, and for fast and economic repairs • Four times faster than traditional methods
The fundamental principle of a Gripple Plus device is simple; there are two channels, each with an independent locking mechanism. The "lock" is created by the roller, which is free to move in one direction only and grips the wire as it moves back. This concept allows tension to be applied throughout the life of the wire.

| | Gripple Plus | | | | | |
|--|---------------|--|---------------|---|------------------|---------------------------------|
| WIRE TYPE | ITEM # | PRODUCT | WIRE DIAMETER | WIRE RANGE (gauge) | MAX. LOAD | PACKAGING & WEIGHT |
| Plain wire / Field Fence (Pre Fab) / Electric Fence | 2881 | Gripple Plus SMALL | 1.40 - 2.20 | 17 -13 | 300kg / 600 lb | 10/pkg 15 pkgs/ctn 11 lbs/ctn |
| | 2882 | Gripple Plus MEDIUM (see below specs for 15'/2 barbed) | 2.00 - 3.25 | 14 - 10 including H.T. 12-1/2 smooth | 400kg / 880 lb. | 20/pkg 10 pkgs/ctn 12.5 lbs/ctn |
| | 2883 | Gripple Plus LARGE | 3.25 - 4.20 | 10 - 7 ¹ / ₂ best for monofilament nylon horse wire | 600kg / 1320 lb | 10/pkg 12 pkgs/ctn 12.6 lbs/ctn |
| | Barbed Grippl | e | | | | |
| High tensile barbed wire 15 ¹ / ₂ ga) | 2882 | Gripple Plus MEDIUM (see above specs for 14-10 ga smooth) | 1.60 - 1.70 | 15 ¹ / ₂ - 15 ga gauge H.T. barbed wire | 400 kg / 880 lbs | 20/pkg 10 pkgs/ctn 12.5 lbs/ctn |
| Mild Steel / Barbed Wire | 2886 | Barbed Wire Gripple | 2.00 - 2.50 | 14 - 12 ¹ / ₂ barbed (smooth 7 - 8 gauge) | 150 kg / 330 lbs | 10/pkg 20 pkgs/ctn 13 lbs/ctn |
| For repairs, splice in a new section of 4 mm / 9 ga smooth wire alongside Gripple Barbed 2886 & Medium Gripple Plus 2882 | | | | | | |
| Gripple Tool | | | | | | |
| | | | | | | |

Installation, maintenance 2885 Grip & repair tool

Gripple Tensioning Tool

Tool used to tension wires once Gripples have been installed. Allows each line wire to be tensioned and re-tensioned individually, optimizing the life of your fence. The torque tensioning tool is lightweight and compact. Ideal for hobby farming. 16" overall • 1 to ctn/shipper • 3.2 lbs.



MEDIUM GRIPPLE® STARTER PAK Contains 50 no. 2882 medium Gripples® and 1 no. 2885 Grippler Tensioning Tool.

ITEM NO. 2430 • 50 #2882 & 1 #2885 to Starter pk • 1 Starter pk to shipper • 8 lbs.

MEDIUM GRIPPLE® PROMO PAK Contains 250 no. 2882 medium Gripples® and

1 no. 2885 Grippler Tensioning Tool.

ITEM NO. 2431 • 250 #2882 & 1 #2885 to Promo pk • 1 Promo pk to shipper • 19 lbs.

GRIPPLE® H-POST KIT


The fastest, simplest, and safest method to build an H-Brace Anchoring System.

- Carries loads up to 2,750 pounds
- · No bending, twisting, or tensioning individual stay wires
- Can be tensioned and re-tensioned

Consists of one large HANG FAST GRIPPLE[®] and ¹¹/₆₄ (.165") diameter x 16' 6" long stainless steel cable. Grippler Tensioning Tool required (not supplied)

ITEM NO. 2436 • 12 assemblies (2 per pack) per shipper • 31 lbs.





ELECTRIC FENCE TESTERS & MISC. PARTS

DIGITAL VOLTMETER for electric fence. Reads up to 9,999 volts. Extremely sensitive and accurate. Powered by 9-volt battery supplied. Imported. ITEM NO. 2411 • 1 to counter pkg • 5 to shipper • 4 lbs.

MULTI-LITE Graduated electric fence tester shows how many volts are on the charger or on the fence line. Voltages are plainly marked on the case from 600 volts to 7,000 volts. ITEM NO. 3360 • 1 per card • 4 to shipper • 1.5 lbs.

FIVE-O-LITE TESTER Graduated electric fence tester actually shows how many volts are on the charger or on the fence line. Voltages are plainly marked on the case from 600 volts to 7,000 volts. Individually carded.

ITEM NO. 1360 • 1 per card • 5 testers to package • 10 testers to shipper • wt 3 lbs.

SINGLE LAMP TESTER Essential to make spot checks in the field. Tells whether fence is working and helps locate faults such as 'opens', 'shorts', and partial grounds. Lamp protected by resistor. ITEM NO. 460 • 1 to counter pkg • 20 to shipper • 2 lbs.

FENCE GUARDIAN / NIGHT LIGHT Bright LED lights with 2 high visibility lenses. Blinks at a regular pulse rate with voltage above 2,000. Below 2,000 volts, the flashing stops. Uses very little power so your fence won't be affected. Can be seen up to 1,000 feet plus. ITEM NO. 2221 • 1 to counter pkg • 4 to shipper • 3 lbs.

WEED CHOPPERS Three and four prong style to fit weed chopper type of electric fence controllers. Specify 3 or 4 prongs. Carded. ITEM NO. • 482-3 • (3 prong) • 10 to ctn. • 1 lb. ITEM NO. • 483-4 • (4 prong) • 10 to ctn. • 1 lb.

FUSES to fit most types of electric fence controllers. Dimensions 1/4" x 11/4". AGC - 1 amp. Check manufacturer's specifications. ITEM NO. 485-1 • 5 to blister card • 20 cds (100) to shipper • 1 lb.

ELECTRIC FENCE FUSED PLUG Two one amp fuses protect controller on

110 volt power. (Fuses not included.) Carded. Imported. ITEM NO. 1624 • 10 cards to inner ctn. • 10 to shipper • 1 lb.







485-1

1624











INSTALLATION ACCESSORIES

LIGHTNING CHOKE New design to reduce the impact of lightning traveling the fence line to the controller. Complete with instructions. (Mounting screws not included). *ITEM NO. 2454 • 1 to counter pkg. • 5 pkgs to shipper • 7 lbs.*

LIGHTNING ARRESTOR KIT Heavy duty, farm tested and proven, electric fence lightning arrestor. Complete with wire clamp, ground rod clamp and mounting screws. Imported.

ITEM NO. LA-112 • 1 to blister pkg • 10 pkgs to shipper • 6 lbs.

Reduces effects from electrical surge through power line, a common cause of controller damage. Use on grounded circuits only. Imported. ITEM NO. 2219 • 1 per card, 5 cards per shipper • 1 lb.

VOLTAGE SPIKE PROTECTOR A must for every 110-V fence controller.

UNDERGROUND & HOOK-UP WIRE Two layers of polyethylene over class III galvanized steel wire. Perfect for underground use and to connect fence charger to fence. Designed for direct burial. Withstands 20,000 volts.

14 GA GALV. CORE WIRE

ITEM NO. 2488 • 50 ft per spool • 5 spls per shipper • 10 lbs. ITEM NO. 2212 • 165 ft per spool • 1 spl per shipper • 6 lbs. ITEM NO. 2212-250 • 250 ft per spool • 1 spl per shipper • 10 lbs. ITEM NO. 2212-500 • 500 ft per spool • 1 spl per shipper • 18 lbs.

121/2 GA GALV. CORE WIRE

ITEM NO. 2277 • 165 ft per spool • 1 spl per shipper • 8 lbs. ITEM NO. 2277-250 • 250 ft per spool • 1 spl per shipper • 11 lbs. ITEM NO. 2277-500 • 500 ft per spool • 1 spl per shipper • 23 lbs.

INSULATOR TUBING Has many uses. Black polyethylene tubing accomodates up to $12^{1/2}$ gauge fence wire. Use under driveways, gates, to insulate one wire from another. Withstands 20,000 volts.

ITEM NO. 2453 • 50 ft • 10 coils to shipper • 11 lbs.

ELECTRIC FENCE SWITCH for outdoor use on electric fence. Install several in

each electric fence for convenience and safety. Switch off areas to allow repairs. Use to change polarity of fence wires. Schematic included.

ITEM NO. 2211 • single throw switch • 10 to shipper • 5 lbs. ITEM NO. 2199 • double throw switch • 10 to shipper • 6 lbs.



LA-112





2488, 2212, 2212-250, 2212-500

2277, 2277-250, 2277-500





ENERGY LIMITER Restricts the flow of current to specific sections of fence that may be shorted by rising water or heavy weed growth. Prevents shorted wire from grounding entire fence. Also known as 'FLOOD GATE CONTROLLER'.

ITEM NO. 2209 • 1 to counter pkg • 5 pkg to shipper • 2 lbs.

GROUND RODS & GROUND CLAMPS The most important part for an effective electric fence installation. Use one to three (or more) ground rods as suggested by the fence controller manufacturer.

DIE CAST ZINC GROUND CLAMP - Blister packed ITEM NO. 2303 • 1 to counter pkg • 10 to shipper • 3 lbs.

HOT DIPPED GALVANIZED STEEL GROUND ROD 5/8" DIA X 6' ITEM NO. 2301-1 • 10 to bundle • 58 lbs.

HOT DIPPED GALVANIZED STEEL GROUND ROD 5/8" DIA X 8' ITEM NO. 2304 • 10 to bundle • 82 lbs.

COPPER GROUND ROD 1/2" DIA X 8' ITEM NO. 3358 • 10 to bundle • 54 lbs.

COPPER CLAD STEEL GROUND ROD 5/8" DIA X 8' ITEM NO. 2457 • 10 to bundle • 85 lbs.

ELECTRIC FENCE WARNING SIGN LARGE. 51/2" x 9". Easily attaches to

wire, Equi Rope and Poly Tape. Black on yellow. Individually labeled. ITEM NO. 3400 • 1 to counter pkg • 10 pkgs (60) to shipper • 1.8 lbs.

Printed on both sides. 4" x 8" with bold black letters on bright yellow laminated vinyl. Two holes to anchor on post or hang from wire. ITEM NO. 1614 • 3 to counter pkg • 20 pkgs (60) to shipper • 1.8 lbs.

PANS & PAILS

PAN Shoats, goats, hogs, dogs...soaking your feet and travel kitty litter pans...there are many uses for these handy pans. 1/8" side walls makes them longer lasting and resistant to damage, destruction, and weather. Black smooth finish. Easily cleaned. Resilient polyethylene.


5-quart utility pan (4.6 liters). Top diameter: 115/8", height: 41/8", bottom diameter: 91/2". 14 ozs. each. ITEM NO. 1566 • 5 gt. pan • packed 12 to shipper • 11lbs.

12-quart utility basin (11.2 litres). Large enough to use when draining oil. Top diameter: 17", height: 41/4", bottom diameter: 131/2", 27 ounces.

ITEM NO. 1604 • 12 qt. pan • packed 12 to shipper • 20 lbs.

DARE pans and pails are hefty and hardy with thicker sidewalls. When filled to capacity they hold their shapes and pour without wobble or flex. Capacities, as rated, are irrevocably guaranteed. Quality materials all the way.

PAIL 10-quart (9.64 litres) best quality polyethylene. Colors: Black, White, Red, Yellow, Green, Burgundy, and Blue. ITEM NO. 1609 • 10 qt. pail • packed 12 to shipper • 15 lbs. • specify color










2303, 2301-1, 3358 2304, 2457







FARM TANK FLOAT VALVES

Universal farm tank watering valves convert tanks or barrels into automatic stock waterers. Requires little attention and keep open tanks filled with freshwater. Adjustable to several heights, they are easily installed by hanging plated brackets over edge of tank. Brackets for Poly tanks included as well. Designed to operate from gravity flow or pressure up to 70 PSI. Installation instructions with each valve.

ALUMINUM HOUSED FLOAT VALVE

Model 1780. Precision die cast outer housing. Durable molded float. Two sets of brackets-fits poly tanks and steel tanks. 300 GPH. ITEM NO. 1780 • each in counter pkg • 6 to shipper • 10.5 lbs.

PLASTIC HOUSED FLOAT VALVE— **ECONOMY MODEL**

Model 798. Low priced, very efficient and reliable. Outer housing molded of high impact resin. Withstands weather and abuse. Durable molded float. Two sets of brackets - fits poly tanks and steel tanks. 300 GPH. ITEM NO. 798 • each in counter pkg • 6 to shipper • 8.5 lbs.

Complies with basic anti-siphoning regulations. Available in diecast aluminum or high impact plastic housing with replaceable non-siphoning unit.

ALUMINUM HOUSED NON-SIPHONING

FLOAT VALVE Precision die-cast aluminum float housing, durable molded float and molded non-siphoning unit. 300GPH. ITEM NO. 1800 • each in carton • 6 to shipper • 11 lbs.

1800



2175

798

PLASTIC HOUSED NON-SIPHONING FLOAT VALVE

Economy Model. Float housing molded of high impact ABS plastic. Has same float and non-siphoning unit as valve listed above. Withstands abuse and weather. Will not corrode. 300 GPH.

ITEM NO. 2175 • each in carton • 6 to shipper • 9 lbs.

REPLACEMENT PARTS

Interior Float Assembly. Neoprene seal. Cotter pin. ITEM NO. 1041 • fits 798, 1780, 2175 & 1800 • 6 to shipper • 2 lbs.

Replaceable Orifices

ITEM NO. 1394 • Standard volume - fits 798 &1780 • no standard shipper ITEM NO. 1252 • Low volume - fits 798 & 1780 • no standard shipper ITEM NO. 1482 • Standard volume - fits 1800 & 2175 • no standard shipper

Non-siphoning Tubular Vent Assembly. Complete tube, valve stem, valve and replacement orifice.

ITEM NO. 1533 • Individually pkd • 6 to shipper • 2 lbs.

Neoprene seal-fits on top of float assembly. ITEM NO. 1770 • No standard shipper





1394, 1252, 1482







1780







PLANOGRAMS & MERCHANDISING

Dare Products offers a variety of stock or customized planograms for every size and type of store. Complete assortments for electric fencing, high tensile fencing, equine fencing, electric fence energizers, wire splicing equipment and more. **Call 1-800-922-3273 or** <u>service@dareproducts.com</u> for a complete listing of marketing materials available.



Example of 12 ft. Electric Fencing Center



Example of 4 ft. High Tensile Fencing Center



Example of 4 ft. Equine Fencing Center



In-store displays available for every need. Electric fence, high tensile, equine and combination displays. (as shown)



1 ft. and 2 ft. display boxes





Box labels and bin tags for most items



How To booklets for High Tensile, Equine Fencing and Electric Fence Installation.















CALL TOLL FREE: 1-800-922-DARE (3273) FAX: (269) 965-3261 E-mail: service@dareproducts.com No voice mail! We welcome all telephone calls.

DARE PRODUCTS, INC.

860 BETTERLY RD./ SPRINGFIELD, MI 49037 USA / PHONE (269) 965-2307 www.dareproducts.com