

GENERAL DESCRIPTION

Valspar Fast Prep™ All-in-one concrete cleaner is formulated to clean, degrease and etch concrete surfaces in one easy step. This product prepares concrete for maximum durability and adhesion of top coats, stains and sealers.

Read directions and cautions thoroughly before using this product.

PRODUCT FEATURES

- Reduces prep time; clean, degrease and etch concrete in one easy step
- Prepares concrete for maximum adhesion of topcoats, stains and sealers
- Ready to use

RECOMMENDED USES

- Garage floors
- Exterior Concrete: Patios, driveways and sidewalks
- Exterior Masonry surfaces

PACKAGING

Packaging:

Gallon – 4 per carton

THINNING

Ready to use on garage floors. For other areas such as patios, driveways, sidewalks etc., mix Fast Prep into 1 gallon of water in a plastic watering can and stir for 1 minute.

CLEANUP

Rinse all tools, material and personal protection with water before storing. Wash affected clothing.

STORAGE AND DISPOSAL

Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, rinse with large amounts of clean water. Dispose of container and/or unused contents in accordance with local, state and federal regulations.

COMPOSITION

Package Fill	Tint Fill	Tint Strength
	(oz./gal.)	
Ready to use	128	

PRODUCT SPECIFICATIONS

Vehicle Type: Organic acid salt and Glycol ethers

Weight/Gallon: 8.77

Flashpoint: 240 ° F

VOC (g/L): Less than 4% VOC

Practical Coverage:

250 sq. ft. /gal. As supplied

500 sq. ft./gal Diluted 1:1 with water

Dry Time @ 77 °F and 50% Relative Humidity

To Touch: 4 hours

To topcoat: 24 hours

Application Temperature – 50-90 °F

SURFACE PREPARATION

General: All surfaces must be free of loose dirt, dust, leaves, dried paint or other debris. Use a stiff bristle broom to sweep the surface.

APPLICATION

Read all label directions and cautions thoroughly before using this product.

Wear rubber boots, rubber gloves and eye protection at all times while using this product. Protect plants and landscaping from direct contact and runoff. Transfer into a plastic watering can. Do not use a metal watering can. Inspect floor for grease and oil stains. Spot apply Fast Prep™ directly to these areas and scrub thoroughly with a stiff brush. Rinse with water. Difficult areas may require a second application and scrubbing. Divide the surface into 10' x 10' sections. Pre-wet surface using a garden hose, avoid puddles. To apply Fast Prep, sweep watering can back and forth as you pour to ensure complete coverage. Using a stiff bristle brush, spread Fast Prep over section completely. It should begin to fizz or bubble, this is normal. Note: If Fast Prep is not fizzing, it is not working. The concrete may have been previously sealed, preventing the Fast Prep from working. The sealers must be totally removed before reapplying Fast Prep. Use the brush to scrub the solution into the surface in 2 directions, perpendicular to each other. Brush thoroughly in short, firm motions over stains and spots. When finished with one section, spray with water and wash away residue. Pre-wet the next 10' x 10' (3 m x 3 m) section and repeat steps. When finished, re-rinse completely with garden hose, washing away loosened material and cleaner residue. Keep rinsing until water runs clean. All loosened powders must be removed or they will interfere with coating adhesion. Allow surface to dry completely, at least 4 hours or overnight, before applying any coating.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead

LIMITED WARRANTY

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.

CAUTIONS

WARNING! VAPOR HARMFUL. CAUSES SEVERE EYE IRRITATION.

WARNING! CONTAINS ORGANIC ACID SALT AND GLYCOL ETHERS. KEEP OUT OF THE REACH OF CHILDREN. VAPOR HARMFUL. May affect the brain or nervous system causing dizziness, headache or nausea. Causes severe eye irritation. Causes skin, nose and throat irritation. May be harmful if absorbed through the skin. Harmful if swallowed. **USE ONLY WITH ADEQUATE VENTILATION.** Avoid breathing vapors. If using indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after each use. **DO NOT TAKE INTERNALLY.** Delayed effect from long-term exposure: Reports of commercial painters have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the vapors may be harmful or fatal. **FIRST AID: EYE CONTACT:** Flush thoroughly with water for at least 15 minutes. If irritation persists, get medical attention.* **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.* **IF SWALLOWED:** Do not induce vomiting. Get medical attention immediately.*
*Call poison control center, hospital emergency room or physician immediately.

CS 1.3 DPM

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

This product contains less than 4% VOC

1191 Wheeling Road, Wheeling, IL 60090
888.313.5569
www.valsparpaint.com
Revised: Sept 2012