

# Flexible Fittings & Pipe Repair Products



## Flexible Fittings

▪ Max. pressure: 4.3 psi

▪ Max. temp.: 140°F

Description	For Pipe Size (in.)	L (in.)	Mfr. Model	Item No.	\$ Each
	3 x 3	4	P1070-33	<b>2ZJ89</b>	13.76
	4 x 4	4	P1070-44	<b>2ZJ90</b>	17.74
	6 x 6	5.91	1070-66	<b>3HDD2</b>	36.95
	8 x 8	5.70	1070-88	<b>3HDD3</b>	56.80
	1 1/4 x 1 1/2	6.88	PDTC-150	<b>2ZU12</b>	5.31
	1 1/4 x 2	6.88	PDTC-215	<b>2ZU13</b>	7.69
	1 1/4	6.88	PTC-150	<b>2ZU14</b>	7.57
	1 1/4	9.50	PFT-150	<b>2ZU11</b>	9.33
	4	12"	TST-4	<b>3HDF1</b>	80.65
	6	15.15"	TST-6	<b>3HDF2</b>	105.40
	4	12"	TSW-4	<b>3HDF3</b>	99.25
	6	15.15"	TSW-6	<b>3HDF4</b>	119.40
	1 1/2	2.13	PNH-150	<b>2ZU19</b>	4.46
	2	2.13	PNH-22	<b>2ZU20</b>	4.41
	3	2.13	PNH-33	<b>2ZU21</b>	4.89
	4	2.13	PNH-44	<b>2ZU22</b>	5.50
	6	7.13	NH-66	<b>3HDC2</b>	26.30
	1 1/2 x 1 1/2	4	1059-150	<b>3HDC3</b>	9.68
	2 x 2	4	1059-22	<b>3HDC4</b>	7.91
	3 x 3	4	1059-33	<b>3HDC5</b>	14.09
	4 x 4	4	1059-44	<b>3HDC6</b>	17.64
	1 1/2 x 1 1/2	4	1060-150	<b>3HDC7</b>	9.68
	2 x 2	4	1060-22	<b>3HDC8</b>	7.91
	3 x 3	4	1060-33	<b>3HDC9</b>	14.09
	4 x 4	4	1060-44	<b>3HDD1</b>	17.64
	1 1/2	2.13	P3001-150	<b>2ZJ87</b>	12.43
	1 1/2 x 1	2.20	3001-110	<b>3HDD9</b>	17.45
	1 1/2 x 1 1/4	1.41	3001-1125	<b>3HDE1</b>	15.95
	2	2.13	P3001-22	<b>2ZJ88</b>	15.99
	2 x 1 1/2	2.13	3001-215	<b>3HDE2</b>	12.89
	3 x 3	2.13	3001-33	<b>3HDE3</b>	19.50
	4 x 3	2.13	3001-43	<b>3HDE4</b>	19.46
	4 x 4	2.13	3001-44	<b>3HDE5</b>	19.16
	1 1/2	2.13	P3000-150	<b>2ZJ83</b>	8.94
	2	2.13	P3000-22	<b>2ZJ84</b>	9.51
	2 1/2	2.13	3000-215	<b>3HDD4</b>	12.26
	3	2.13	P3000-33	<b>2ZJ85</b>	12.35
	4	2.13	P3000-44	<b>2ZJ86</b>	15.11
	4 x 3	2.13	3000-43	<b>3HDD5</b>	20.53
	5	3	3000-55	<b>3HDD6</b>	35.25
	6	3	3000-66	<b>3HDD7</b>	47.10
	8	3.80	3000-88	<b>3HDD8</b>	60.15

PVC couplings flex to fit for easy hookup; resist corrosion, rot, and degradation from sunlight and chemicals. To quickly install no hub couplings, use cordless No Hub Coupling Drill Driver No. 5HXN2.

Description	For Pipe Size (in.)	L (in.)	Mfr. Model	Item No.	\$ Each
	1 1/2	0.82	QB-150/125	<b>3HDE6</b>	4.04
	2	1.88	QB-215	<b>3HDE7</b>	3.60
	3	2.31	QB-32	<b>3HDE8</b>	6.26
	4	3	QB-43	<b>3HDE9</b>	13.41
	1 1/2	—	PQC-101	<b>2ZU15</b>	6.88
	2	—	PQC-102	<b>2ZU16</b>	4.89
	3	—	PQC-103	<b>2ZU17</b>	6.17
	4	—	PQC-104	<b>2ZU18</b>	7.84
	5	—	QC-105	<b>3HDA9</b>	11.58
	6	—	QC-106	<b>3HDC1</b>	11.90
	1 1/2	4.75	PQL-150	<b>2ZJ97</b>	16.56
	2	5	PQL-200	<b>2ZJ98</b>	17.61
	3	8	PQL-300	<b>2ZJ99</b>	26.75
	4	10	PQL-400	<b>2ZU10</b>	39.70
	1 1/2	5.50	PQT-150	<b>2ZJ93</b>	20.72
	2	7.50	PQT-200	<b>2ZJ94</b>	22.29
	3	10	PQT-300	<b>2ZJ95</b>	34.85
	4	13.13	PQT-400	<b>2ZJ96</b>	47.70
	1 1/2 x 1 1/4	3.43	P1056-150/125	<b>4P004</b>	5.55
	2 x 1 1/2	3.50	P1056-215	<b>4P006</b>	6.17
	3 x 1 1/2	4	1056-315	<b>3HCY6</b>	8.79
	3 x 2	4	P1056-32	<b>4P008</b>	7.23
	4 x 1 1/2	3.96	1056-415	<b>3HCY7</b>	13.01
	4 x 2	3.88	1056-42	<b>3HCY8</b>	11.79
	4 x 3	4	P1056-43	<b>4P010</b>	9.89
	5 x 2	4	1056-52	<b>3HCY9</b>	22.13
	5 x 3	3.90	1056-53	<b>3HCZ1</b>	18.95
	5 x 4	3.95	1056-54	<b>3HCZ2</b>	16.05
	6 x 2	6	1056-62	<b>3HCZ4</b>	40.60
	6 x 3	5.75	1056-63	<b>3HCZ5</b>	32.20
	6 x 4	5.75	1056-64	<b>3HCZ6</b>	21.43
	6 x 5	5.77	1056-65	<b>3HCZ7</b>	22.70
	8 x 4	5.99	1056-84	<b>3HCZ9</b>	61.60
	8 x 6	5.99	1056-86	<b>3HDA1</b>	33.75
	10 x 8	5.98	1056-10-8	<b>3HDA3</b>	41.10
12 x 10	6.37	1056-1210	<b>3HDA5</b>	51.75	
	3/4 x 3/4	2.38	P1056-075	<b>2ZJ91</b>	7.59
	1 x 1	2.40	P1056-100	<b>2ZJ92</b>	7.59
	1 1/4 x 1 1/4	3.45	P1056-125	<b>4P003</b>	4.90
	1 1/2 x 1 1/2	3.43	P1056-150	<b>4P005</b>	4.88
	2 x 2	3.45	P1056-22	<b>4P007</b>	5.55
	3 x 3	3.98	P1056-33	<b>4P009</b>	6.53
	4 x 4	4.02	P1056-44	<b>4P011</b>	8.75
	5 x 5	3.97	1056-55	<b>3HCZ3</b>	14.49
	6 x 6	5.74	1056-66	<b>3HCZ8</b>	19.69
	8 x 8	6.04	1056-88	<b>3HDA2</b>	28.10
10 x 10	5.89	1056-1010	<b>3HDA4</b>	37.50	
12 x 12	6.32	1056-1212	<b>3HDA6</b>	46.55	
15 x 15	10	1056-1515	<b>3HDA7</b>	72.15	
18 x 18	9.80	1056-1818	<b>3HDA8</b>	146.65	

## Pow-R™ Pipe Repair Products

▪ EPA-approved for use on drinking water lines; Certified to ANSI/NSF 61

Hand-workable epoxy cures as hard as steel to create permanent, industrial-strength repairs. Simply apply putty, soak wrap, wrap pipe, and tighten for approximately 15

min.; sets in 30 min. Holds tight, even under water. Kits include all necessary tools. Uses: Use on fluid-bearing pipes made from copper, plastics, PVC, rubber, fiberglass, galvanized, concrete, and more.



Description	Size (in.)	Line Pressure (psi)	Heat Resistant (Deg. F)	Item No.	\$ Each	
<b>Pow-R Wrap™ Pipe Repair System</b>	For Pipe up to 1" Dia.	2 x 48	600	1197	<b>2KUT3</b>	13.26
	For Pipe 1 1/4 to 3" Dia.	3 x 132	600	1197	<b>2KUT4</b>	30.50
	For Pipe 3 to 6" Dia.	4 x 252	600	1197	<b>2KUT5</b>	51.80
<b>Pow-R Patch® Multi-Surface Repair Kit</b>	Fiberglass and Epoxy Patch	4 x 6	100	425	<b>3HCX8</b>	11.58
<b>Pow-R Pack® Universal Plumbing, Pipe and Hose Repair Kit</b>	Includes 1 Pow-R Wrap 2 x 48", 1 Pow-R Patch, 1 Pow-R Stick (Gray), and 2-Pair Protective Gloves	2 x 48 Wrap, 4 x 6 Patch	600 Wrap, 100 Patch	392	<b>3HCY4</b>	30.30



No. 2KUT3



No. 3HCX8



No. 3HCX9



No. 3HCY4

Description	Color	Size	Max. Temp. (°F)	Item No.	\$ Each
<b>Pow-R Stick®</b>					
Steel Reinforced Epoxy Putty	Copper	1.33 oz.	392	<b>3HCX9</b>	3.64
Steel Reinforced Epoxy Putty	Gray	1.33 oz.	392	<b>3HCY1</b>	3.64
Steel Reinforced Epoxy Putty	White	1.33 oz.	392	<b>3HCY2</b>	3.64
3 Pack Steel Reinforced Epoxy Putty	Copper, Gray and White	1.33 oz. Each	392	<b>3HCY3</b>	10.50