

CLICK SEAL[®]

Faucet Connectors

The "CLICK"
Lets You Know
It's Sealed![™]

- Only Fluidmaster Click Seal[®] connectors click and stop tightening when the nut has achieved a perfect seal
- Durable brass thread
- Stainless steel braiding provides maximum protection against bursting
- Prevents overtightening
- Easy to install, no tools necessary
- Patent-pending Click Seal[®] technology
- Lead-free certified




Patent-pending
Click Seal[®] technology

Durable
brass thread

Stainless
steel braid

CLICK SEAL[®]



INSTALLATION INSTRUCTIONS

1. Turn off water supply at shutoff valve.
2. Remove old supply connector and clean all connection threads.
3. Prior to threading 1/2" or 3/8" nut to shutoff valve, turn Click Seal[®] nut counterclockwise until threads align. Gently turn Click Seal[™] nut clockwise and hand-tighten until nut clicks. The "click" lets you know it's sealed!
4. Prior to threading 1/2" black metal nut to faucet inlet connection, turn Click Seal[®] nut counterclockwise until threads align. Gently turn Click Seal[®] nut clockwise and hand-tighten until nut clicks. The "click" lets you know it's sealed!
5. Slowly turn on water at the shutoff valve.
6. Carefully check for leaks.

Burst Strength: Up to 1,000 PSI

Torque Rating: 14-22 in-lbs

CONNECTOR CONFIGURATION	MODEL NUMBER	LENGTH (inches)	CASE QTY	CASE DIMENSIONS W/D/H (inches)	CASE WEIGHT (LBS)	UPC 0 39961	SCCI 2of5 100 39961
3/8" Female Compression x 1/2" F.I.P.	B1F12CS	12	25	16.5 x 8.0 x 4.5	7.0	00493 2	00493 9
3/8" Female Compression x 1/2" F.I.P.	B1F16CS	16	25	21.6 x 8.6 x 4.5	8.0	00494 9	00494 6
3/8" Female Compression x 1/2" F.I.P.	B1F20CS	20	25	21.6 x 8.6 x 4.5	9.0	00511 3	00511 0
3/8" Female Compression x 1/2" F.I.P.	B1F30CS	30	25	21.5 x 8.2 x 5.8	11.0	00495 6	00495 3
1/2" F.I.P. x 1/2" F.I.P.	B4F12CS	12	25	16.5 x 8.0 x 4.5	7.0	00496 3	00496 0
1/2" F.I.P. x 1/2" F.I.P.	B4F16CS	16	25	21.6 x 8.6 x 4.5	8.0	00497 0	00497 7
1/2" F.I.P. x 1/2" F.I.P.	B4F20CS	20	25	21.6 x 8.6 x 4.5	9.0	00499 4	00499 1
1/2" F.I.P. x 1/2" F.I.P.	B4F30CS	30	25	21.6 x 8.6 x 5.8	11.0	00510 6	00510 3
3/8" C, 7/16" C, 11/2" F.I.P. x 1/2" F.I.P.	4F16UCSR	16	10	8.0 x 16.5 x 4.5	6.5	00329 4	00329 1
3/8" Female Compression x 1/2" F.I.P.	B1F20CSR	20	10	6.5 x 22.0 x 4.0	5.5	00512 0	00512 7

Fluidmaster, Inc. at 30800 Rancho Viejo Road, San Juan Capistrano, CA 92675, (949) 728-2000, Fax (949) 728-2205.

Red/Green color arrangement is a registered trademark of Fluidmaster, Inc.

© 2012 Fluidmaster, Inc. ® Registered trademark of Fluidmaster, Inc.

U.S. and Other Patents Pending.

06/12 FM91429 Rev.1

 **Fluidmaster**[®]