

J-B Weld Product Facts



J-B Weld – Mfr Part # 8265-S

- An alternative to welding, soldering, and brazing.
- Will bond to most clean and dry surfaces and sets in 1-2 hours and will fully cure in 16-24 hours.
- Waterproof, petroleum, chemical, and acid resistant when fully cured.
- It can be drilled, tapped, machined, filed, sanded, and painted.
- Super strong, non-toxic, and temperature resistant up to 600°F.



J-B KwikWeld – Mfr Part # 8276

- J-B Kwik is a fast set - cure version of J-B Weld that will set in 4 minutes and fully cure in 4-6 hours.
- Waterproof, petroleum, chemical, and acid resistant once fully cured.
- Non-toxic and is temperature resistant up to 300°F.
- Can be used on almost any surface - bronze, porcelain, ceramic, marble, glass, wood, concrete, fiberglass, steel, iron, copper, aluminum, ABS & PVC plastics.
- When fully cured J-B Kwik can be drilled, tapped, machined, filed, sanded and painted.



J-B SteelStik – Mfr Part # 8267-S

- Steel Reinforced Epoxy Putty Stick.
- Hand kneadable epoxy adhesive will plug holes and make permanent repairs on wet and dry surfaces.
- Cures completely submerged in gasoline or under water in 60 minutes.
- Can be drilled, sanded, filed, tapped, machined and painted.
- Bonds to virtually any surface including metal, wood and plastic.



J-B Waterweld – Mfr Part # 8277

- Make permanent repairs in moist or under water applications.
- Waterweld will fully cure in 60 minutes and will adhere to most any surface.
- Once cured Waterweld can be drilled, sanded, filed, tapped, machined and painted.
- Turns do-it-yourselfers into repair professionals.



J-B PlasticWeld – Mfr Part # 8237

- Repair and rebuild any rigid and semi-flexible plastic including ABS, PVC and CPVC.
- Rebuild automotive trim, fiberglass parts and vinyl siding.
- Bonds instantly with superior strength and does not shrink or pull away.
- Sets in 20 minutes. Drinking water safe.



“World’s finest cold weld compound”

J-B Weld Product Facts



J-B KwikWood – Mfr Part # 8257

- Repair and rebuild anything made of wood.
- Hand-mixable epoxy putty stick for interior and exterior wood.
- Ideal for damaged or rotted sections of wood on doors, windows, fences, shutters and more.
- Cures within an hour. Can be drilled, tapped, sanded, painted or stained.
- 2-part wood epoxy (compared to a one component wood filler), KwikWood will not shrink, crack, separate or pull away.
- *Ideal for filling in stripped screws or replacing door hinges in one hour. Stronger than the wood.*



J-B WoodWeld Wood Epoxy Adhesive – Mfr Part # 8251

- 2 part Quick Setting Wood Epoxy Adhesive.
- Superior adhesion and stronger than the wood itself.
- Repairs anything made of wood. Sets in 6-8 minutes. No clamping necessary.
- Interior and exterior. Will not shrink, separate or crack.
- J-B WoodWeld Epoxy chemically cures – uniformly and consistently. No mess.
- Will not foam or expand like urethane-based wood glues.



J-B MarineWeld – Mfr Part # 8272

- Bonds to just about any porous and non-porous material.
- MarineWeld is impervious to saltwater, petroleum, chemical, and acid resistant once fully cured.
- It can be drilled, tapped, machined, file, sanded, and painted.
- Every boat afloat should carry MarineWeld for quick and permanent repairs.



J-B Kwik Professional Size – Mfr Part # 8270

- The same as our J-B Kwik in a convenient 10 oz. “shop size”.
- Great economical alternative for installers, contractors, machine shops, or the do-it-yourselfer who uses a lot of our product.
- J-B Kwik Professional Size makes strong, permanent repairs when hot welding isn't possible or practical.



J-B Weld Professional Size – Mfr Part # 8280

- The same as our J-B Weld in a convenient 10 oz. “shop size”.
- Great economical alternative for installers, contractors, machine shops, or the do-it-yourselfer who uses a lot of our product.
- J-B Weld Professional Size makes strong, permanent repairs when hot welding isn't possible or practical.

J-B Weld Product Facts



Perm-O-Seal – Mfr Part # DS-114

- Non-toxic mixture designed to permanently seal holes and cracks in radiators, water jackets and cylinder heads.
- Contains rust inhibitors and water pump lubricants that help the radiator operate at peak efficiency.
- Just pour Perma-O-Seal into the radiator while the engine is running – it speeds the water channels, seeks out holes, and swells as soon as it comes in contact.



J-B Weld Perma-Lock ThreadLockers

Mfr Part # Red 6 ml 27106, 13 ml 27113, 36 ml 27136

Mfr Part # Blue 6 ml 24206, 13 ml 24213, 36 ml 24236

- Seals the threads against leakage and prevents rust and corrosion.
- Temperature resistant to 300° F. OEM approved.
- No spill, drip or clog cap.



J-B Weld High Heat – Mfr Part # 8297

- 3 times stronger than conventional epoxy putty sticks.
- Intermittent heat up to 500° F.
- Great for exhaust manifolds, tail pipes, mufflers, engine blocks, duct work and high temperature projects.



J-B Mini – Mfr Part # 8212-S

- Up to 10 times the strength of super glues.
- Comes in an easy to use 6 ml. syringe.
- Once mixed, the clear epoxy compound will set up in 4 minutes and fully cure in 2-4 hours.
- Make quick repairs to wood, tile, and ceramics, jewelry, glass, metals, PVC and ABS plastics.

**the most durable cold weld products available...
products that are not only the best sellers in their respective
categories, but which also provide cost-effective repair options –
even on items most people think can not be repaired!**