


STANLEY

BOSTITCH[®]










2010 CONSTRUCTION FASTENER LIST

Tool Reference Chart

 H	 G&H	 A&B	 C&D	 A&B	 D
BRT130	F21PL2	F28WW	F33PT	GF28WW	MCN150
 D	 E&X	 E	 E	 F	 J
MCN250	N75C	N80CB	N89C	N89C-HQ	438S2R
 I	 N	 M	 N	 K	 M
RN46-1	BT1855K	FN1664K	GBT1850K	GFN1564K	GFN1664K
 P	 K	 N&O	 N	 O	 M
HP118K	N62FNK-2	SB-2IN1	SB-1850BN	SB-150SX	SB-1664FN
 O	 O&T	 S	 R	 Y	 R
SX1838K	EHF1838K	LHF2025K	MFN-201	MIII812CNCT	MIIIFN
 Q	 U,W&X	 U&X			 V&W
MIIIFS	N66BC	N66C	PN50	PN100K	SL1838BC
 J	 Z	 J	 Z	 AA	 CC
438S2	438S4-1	450S2-1	650S4	650S5	H30-6
 BB	 BB	 DD	 CC	 BB	 EE
H30-8	H30-8D6	P3-CHROME	P6C-6	PC6-8	P7
 CC	 CC	 BB&CC	 BB		
PC2K	T6-60C2	T6-8	T6-80C2		

TABLE OF CONTENTS


This catalog was designed with a color-coding system. Finding the right tool and fastener for the right application is as easy as flipping to the appropriate color.

	FRAMING	4-8
	ROOFING	9
	FINISH AND TRIM	10-11
	FLOORING	12
	SPECIALTY	13-14
	CONSTRUCTION STAPLES	15
	MANUAL FASTENING	16


Stanley®-Bostitch® manufactures over 2000 types of fasteners. Each fastener is engineered for optimal performance in Stanley®-Bostitch® tools, and for exceeding the performance expectations of our customers. Our goal is to continually increase efficiency, productivity, and quality, and to ensure building code compliance through reports ESR-1539, ESR-1482, ESR-2122 and ER-120. Our team of engineers leads the industry in innovation and design. Utilizing our advanced laboratory, our team of engineers conducts **environmental testing** to study the effects of storm forces and other weather conditions, **withdrawal testing** to evaluate new coatings, **penetration testing** to evaluate drive characteristics, and **development testing** to optimize withdrawal, shear and pull-through performance.

Selecting the Proper Stanley®-Bostitch® Nails


Examples of Stanley®-Bostitch® Stick Nails




Plastic Collation



Wire Collation




Paper Collation




Adhesive Collation

Stanley®-Bostitch® Stick Nails are designed, engineered and manufactured in four different forms and are generally identified by collation material – plastic, wire, paper or adhesive. Adhesive collation is used on finish nails and brads for trim and fine woodworking. Finish nails and brads range in length from 3/8" to 2-1/2" with diameters ranging from 15 to 23 gauge. The plastic, wire and paper collated nails are used for general framing and crating applications. Stick nails range in length from 1-1/2" to 6-1/4" with diameters ranging from 0.113" to 0.165".

Examples of Stanley®-Bostitch® Coil Nails




Wire Collation



Plastic Collation


Stanley®-Bostitch® Coil Nails are made at a 15-degree angle, joined together with wire or plastic, and range from 3/4" to 4" in length with diameters ranging from 0.080" to 0.148". Applications typically include roofing, siding, fencing, framing and crating.



There are four types of **nail shanks** – smooth, ring, screw and HurriQuake®. A **smooth shank** has a withdrawal capacity that is adequate for most applications. During the manufacturing of smooth shank nails, a coating is applied, which eases penetration resistance and ultimately helps improve the holding power of the fastener. However, when more holding power is necessary, a ring or screw shank should be used. A **ring shank** is designed for increased withdrawal strength in softwoods. The **screw shank** works well at improving the withdrawal capacity in hardwoods. The **HurriQuake®** nail combines all three shanks for high performance sheathing and framing.

The metal and coating used on the shank of the nail are important when selecting the proper nail for the application. Bostitch offers nails manufactured out of cold worked carbon steel, cold worked hardened steel, aluminum and stainless steel. Cold worked carbon steel is most commonly used when corrosion resistance is not a concern; cold worked hardened steel is most commonly used when attaching material to very hard substrates; and aluminum and stainless steel are most commonly used when severe corrosion resistance is needed due to the wood or environment in which the nail is installed.


Exclusive to Bostitch is the THICKCOAT® galvanization which provides a consistent, high-performance, corrosion-resistant coating. Bostitch THICKCOAT®, as recognized in the exclusive code report ESR-1482, is designed to meet or exceed the performance of ASTM A153 hot dipped galvanized nails. THICKCOAT® fasteners are available in most popular sizes of wire weld, coil and stick, and are specifically designed for use in ALL pressure treated lumber and exterior applications.



Shear Shank Technology (Patent-Pending)

- Screw shank fills voids in sheathing created by rings
- Smooth shank provides shear strength at primary stress points

- Deep Ring Technology**
- Ring shank delivers outstanding holding power



Easy to Identify Head


- Marked for easy identification during code inspection

Up to 25% Larger Effective Head Area (Patented)

- Increases pull-through resistance
- Designed to decrease overdrive


Nail Point

There are four basic point styles to consider for an application – diamond, blunt diamond, chisel, and blunt chisel. Proper selection is important as the nail point can cause the wood to split, rob the tool of power or affect the withdrawal capacity of the nail.




Diamond Point

General purpose point with best holding power




Blunt Diamond Point

Effective at helping to reduce wood splitting in hardwood applications



Chisel Point


Preferred point for trim applications



Blunt Chisel Point

Effective at helping to reduce wood splitting in hardwood applications

Selecting the proper Stanley®-Bostitch® Staples



All staples are joined with an adhesive coating that holds the staple together, aids the staple in penetration and keeps it from withdrawing from the wood. Light wire staples are measured in thousandths and heavy wire staples are measured by gauge. Staple gauges range from 15 to 18 and the lengths range from 1/2" to 2-1/2". Both light wire and heavy wire staples are available in steel, coated, and stainless steel, and are typically classified by the crown width. In some cases, staples are less expensive and may reduce material splitting as compared to nails.

CONSTRUCTION FASTENERS

A. 28° Wire Weld Full Round Head Stick Framing Nails

SKU #	SIZE	SHANK	FINISH	POINT STYLE	QUANTITY	FITS
S6D-FH	2" x .113"	Smooth	Coated	Diamond	2000	BOSTITCH® N79WW, N80SB, N86S, N88WWB, N100S, F28WW, GF28WW
S6DGAL-FH	2" x .113"	Smooth	Thickcoat®	Diamond	2000	
S6DR113-FH	2" x .113"	Ring	Coated	Diamond	2000	
S6DR113GAL-FH	2" x .113"	Ring	Thickcoat®	Diamond	2000	
S8D-FH	2-3/8" x .120"	Smooth	Coated	Diamond	2000	
S8DGAL-FH	2-3/8" x .120"	Smooth	Thickcoat®	Diamond	2000	
S8DR-FH	2-3/8" x .120"	Ring	Coated	Diamond	2000	
S8DRGAL-FH	2-3/8" x .120"	Ring	Thickcoat®	Diamond	2000	
S8DS-FH	2-3/8" x .113"	Screw	Coated	Diamond	2000	
S8D131-FH	2-1/2" - .131"	Smooth	Coated	Diamond	2000	
S10D-FH	3" x .120"	Smooth	Coated	Diamond	2000	
S10DGAL-FH	3" x .120"	Smooth	Thickcoat®	Diamond	2000	
S10DR-FH	3" x .120"	Ring	Coated	Diamond	2000	
S10DRGAL-FH	3" x .120"	Ring	Thickcoat®	Diamond	2000	
S10DS-FH	3" x .120"	Screw	Coated	Diamond	2000	
S10DSGAL-FH	3" x .120"	Screw	Coated	Diamond	2000	
S10D131-FH	3" x .131"	Smooth	Coated	Diamond	2000	
S12D-FH	3-1/4" x .120"	Smooth	Coated	Diamond	2000	
S12DGAL-FH	3-1/4" x .120"	Smooth	Thickcoat®	Diamond	2000	
S12DS-FH	3-1/4" x .120"	Screw	Coated	Diamond	2000	
S12DSGAL-FH	3-1/4" x .120"	Screw	Thickcoat®	Diamond	2000	
S12D131-FH	3-1/4" x .131"	Smooth	Coated	Diamond	2000	
S12DR131-FH	3-1/4" x .131"	Ring	Coated	Diamond	2000	
S16DS-FH	3-1/2" x .131	Screw	Coat	Diamond	2000	
S16D131-FH	3-1/2" x .131"	Smooth	Coated	Diamond	2000	
S16D131GAL-FH	3-1/2" x .131"	Smooth	Thickcoat®	Diamond	2000	

ALSO FITS Porter-Cable FM350A

B. 28° Wire Weld Stick Framing Nails

SKU #	SIZE	SHANK	FINISH	POINT STYLE	QUANTITY	FITS
S8DSS-1M	2-3/8" x .113"	Smooth	Stainless	Diamond	1000	BOSTITCH® N79WW, N80SB, N86S, N88WWB, N100S, F28WW, GF28WW
S8DRSS-1M	2-3/8" x .113"	Ring	Stainless	Diamond	1000	
S8DH	2-1/2" x .131	Smooth	Hardened	Diamond	2000	
S12DSS-1M	3-1/4" x .120"	Smooth	Stainless	Diamond	1000	
S16DSS-1M	3-1/2" x .120"	Smooth	Stainless	Diamond	1000	

ALSO FITS Porter-Cable FM350A



C. 33° Paper Collated Stick Framing Nails

SKU #	SIZE	SHANK	FINISH	POINT STYLE	QUANTITY	FITS
PT-S6D113EP	2" x .113"	Smooth	Coated	Diamond	5000	BOSTITCH® F33PT, GF33PT, N90PT
PT-S6DR113EP	2" x .113"	Ring	Coated	Diamond	5000	
PT-S8D113EP	2-3/8" x .113"	Smooth	Coated	Diamond	5000	
PT-S8D113HDG	2-3/8" x .113"	Smooth	Hot Dipped	Diamond	5000	
PT-S8DR113EP	2-3/8" x .113"	Ring	Coated	Diamond	5000	
PT-S8DR113HDG	2-3/8" x .113"	Ring	Hot Dipped	Diamond	5000	
PT-S10D120EP	3" x .120"	Smooth	Coated	Diamond	3000	
PT-S10D120HDG	3" x .120"	Smooth	Hot Dipped	Diamond	3000	
PT-S10DR120HDG	3" x .120"	Ring	Hot Dipped	Diamond	3000	
PT-S10D131EP	3" x .131"	Smooth	Coated	Diamond	3000	
PT-S12D120EP	3-1/4" x .120"	Smooth	Coated	Diamond	3000	
PT-S12131EP	3-1/4" x .131"	Smooth	Coated	Diamond	2500	
PT-S12D131HDG	3-1/4" x .131"	Smooth	Hot Dipped	Diamond	2500	
PT-S16D131EP	3-1/2" x .131"	Smooth	Coated	Diamond	2500	
PT-S16D131HDG	3-1/2" x .131"	Smooth	Hot Dipped	Diamond	2500	

ALSO FITS
ATRO CHS933 • **DEWALT** D51823 • **Paslode** 5300S, 5325S, 5350S, SL312, F350S, IM325, IMCT325, IM350
Hitachi NV83A • **Porter-Cable** F350 • **Ridgid** R350CHA • **Senco** SN2+, SN3, SN325+, SN4, SN70, FramePro

D. STRAPSHOT™ 35° Paper Collated Metal Connector Nails

SKU #	SIZE	SHANK	FINISH	POINT STYLE	QUANTITY	FITS
PT-MC13115-1M	1-1/2" x .131"	Smooth	Brite Heat Treated	Diamond	1000	BOSTITCH® F33PT, MCN150, MCN250
PT-MC13115G-1M	1-1/2" x .131"	Smooth	Brite Heat Treated	Diamond	1000	
PT-MC14815-1M	1-1/2" x .148"	Smooth	Brite Heat Treated	Diamond	1000	
PT-MC14815G-1M	1-1/2" x .148"	Smooth	Brite Heat Treated	Diamond	1000	
PT-MC13125-1M	2-1/2" x .131"	Smooth	Brite Heat Treated	Diamond	1000	BOSTITCH® F33PT, MCN250
PT-MC13125G-1M	2-1/2" x .131"	Smooth	Brite Heat Treated	Diamond	1000	
PT-MC14825-1M	2-1/2" x .148"	Smooth	Brite Heat Treated	Diamond	1000	
PT-MC14825G-1M	2-1/2" x .148"	Smooth	Brite Heat Treated	Diamond	1000	
PT-MC16225-1M	2-1/2" x .162"	Smooth	Brite Heat Treated	Diamond	1000	
PT-MC16225G-1M	2-1/2" x .162"	Smooth	Brite Heat Treated	Diamond	1000	

ALSO FITS
Hitachi NR65AK • **Paslode** F250S-PP • **Rap-A-Nail** RN150, RN250

CONSTRUCTION FASTENERS

FRAMING

E. 15° Coil Framing Nails


SKU #	SIZE	SHANK	FINISH	POINT STYLE	QUANTITY	FITS
C4PSTIF	1-1/2" x .099"	Smooth	Stiff	Diamond	3600	BOSTITCH N75C, N80CB
C4DCSBALG	1-3/8"	Screw	Galvanized	Ballistic	3600	
AC4D113BDP	1-1/2" x .113"	Smooth	Coated	Blunt Diamond	7500	
C6P99D	2" x .099"	Smooth	Coated	Diamond	3600	BOSTITCH N80CB, N89C, N100C, N75C
C6P99DG	2" x .099"	Smooth	Thickcoat®	Diamond	3600	
C6R99BC	2" x .099"	Ring	Coated	Blunt Chisel	3600	
C6R99BCG	2" x .099"	Ring	Thickcoat®	Blunt Chisel	3600	
C6R99BDSS	2" x .099"	Ring	Stainless	Blunt Diamond	3600	
C7R99BCG	2-1/4" x .099"	Ring	Thickcoat®	Blunt Chisel	3600	
C7PSTIF	2-1/4" x .099"	Smooth	Stiff	Diamond	3600	
C8P99D	2-1/2" x .099"	Smooth	Coated	Diamond	3600	
C8P99DG	2-1/2" x .099"	Smooth	Thickcoat®	Diamond	3600	
C8R99BCG	2-1/2" x .099"	Ring	Thickcoat®	Blunt Chisel	3600	
C8R99BD	2-1/2" x .099"	Ring	Coated	Blunt Diamond	3600	
C8R99BDSS	2-1/2" x .099"	Ring	Stainless	Blunt Diamond	3600	
C8R113DG	2-3/8" x .113"	Smooth	Thickcoat®	Diamond	2700	
C8P120D	2-1/2" x .120"	Smooth	Coated	Diamond	2700	
C8P131D-4.5M	2-1/2" x .131"	Smooth	Coated	Diamond	4500	
C10P120D	3" x .120"	Smooth	Coated	Diamond	2700	
C10P120DG	3" x .120"	Smooth	Thickcoat®	Diamond	2700	
C10P131D	3" x .131"	Smooth	Coated	Diamond	2700	
C10P131DG	3" x .131"	Smooth	Thickcoat®	Diamond	2700	
C10P148D-SHORT	2-1/4" x .148"	Smooth	Coated	Diamond	2700	
AC10DR	3" x .120"	Ring	Coated	Blunt Diamond	4500	
C10R120DSS	3" x .120"	Ring	Stainless	Diamond	2700	
C10S120DG	3" x .120"	Screw	Thickcoat®	Diamond	2700	
C12P120D	3-1/4" x .120"	Smooth	Coated	Diamond	2700	BOSTITCH N80CB, N89C, N100C
C12P120DG	3-1/4" x .120"	Smooth	Thickcoat®	Diamond	2700	
C12R120DSS	3-1/4" x .120"	Ring	Stainless	Diamond	2700	
AC12DS	3-1/4" x .120"	Screw	Coated	Blunt	4500	
C12S120DG	3-1/4" x .120"	Screw	Thickcoat®	Diamond	2700	
C12P131D	3-1/4" x .131"	Smooth	Coated	Diamond	2700	BOSTITCH N89C, N100C
C16P131D	3-1/2" x .131"	Smooth	Coated	Diamond	2700	
C16P131DG	3-1/2" x .131"	Smooth	Thickcoat®	Diamond	2700	BOSTITCH N100C, N100CPP, N400C
C20S120D	4" x .120"	Screw	Coated	Diamond	2700	
C20P131D	4" x .131"	Smooth	Coated	Diamond	2700	
C20P131DG	4" x .131"	Smooth	Thickcoat®	Diamond	2700	

ALSO FITS

DUOFAST CNW-75 • Hitachi NV83A • Makita AN901 • Max 890C • Paslode F275C, P275C, F325C, P325C, 5300C • Porter-Cable Coil350 • Senco SCN60, SCN65



F. High-Performance Coil Framing and Sheathing Nails

SKU #	SIZE	SHANK	FINISH	POINT STYLE	QUANTITY	FITS
C8DR113-HQ	2-1/2" x .113"	HurriQuake®	Coated	Diamond	4500	BOSTITCH® N89C-HQ 
C8DR131-HQ	2-1/2" x .131"	HurriQuake®	Coated	Diamond	4500	
C10DR113-HQ	3" x .113"	HurriQuake®	Coated	Diamond	4500	
C10DR131-HQ	3" x .131"	HurriQuake®	Coated	Diamond	4500	

G. 21° Plastic Collated Metal Connector Nails

SKU #	SIZE	SHANK	FINISH	POINT STYLE	QUANTITY	FITS
RH-MC13115-S	1-1/2" x 0.131"	Smooth	Brite Heat Treated	Diamond	1000	BOSTITCH® N88RH-2MCN, F21PL, F21PL2
RH-MC13115GAL-S	1-1/2" x 0.131"	Smooth	Thickcoat® Heat Treated	Diamond	1000	
RH-MC14815-S	1-1/2" x 0.148"	Smooth	Brite Heat Treated	Diamond	1000	
RH-MC14815GAL-S	1-1/2" x 0.148"	Smooth	Thickcoat® Heat Treated	Diamond	1000	
RH-MC14825-S	2-1/2" x 0.148"	Smooth	Brite Heat Treated	Diamond	900	
RH-MC16225-S	2-1/2" x 0.162"	Smooth	Brite Heat Treated	Diamond	900	
RH-MC16225GAL-S	2-1/2" x 0.162"	Smooth	Thickcoat® Heat Treated	Diamond	900	

CONSTRUCTION FASTENERS

FRAMING

H. 21° Plastic Collated Full Round Head Framing Nails

SKU #	SIZE	SHANK	FINISH	POINT STYLE	QUANTITY	FITS
RH-S6DEP	2" x .113"	Smooth	Coated	Diamond	6000	BOSTITCH® N88RH, F21PL, F21PL2
RH-S6DHDG	2" x .113"	Smooth	Hot Dipped	Diamond	6000	
RH-S6DRHDG	2" x .113"	Ring	Hot Dipped	Diamond	6000	
RH-S214DEP	2-1/4" x .148"	Smooth	Coated	Diamond	4000	
RH-S8D113EP	2-3/8" x .113"	Smooth	Coated	Diamond	5000	
RH-S8D113HDG	2-3/8" x .113"	Smooth	Hot Dipped	Diamond	5000	
RH-S8DR113EP	2-3/8" x .113"	Ring	Coated	Diamond	5000	
RH-S8DR113HDG	2-3/8" x .113"	Ring	Hot Dipped	Diamond	5000	
RH-S8D120EP	2-3/8" x .120"	Smooth	Coated	Diamond	5000	
RH-S8D131EP	2-1/2" x .131"	Smooth	Coated	Diamond	5000	
RH-S8D131HDG	2-1/2" x .131"	Smooth	Hot Dipped	Diamond	5000	
RH-S10D120EP	3" x .120"	Smooth	Coated	Diamond	4000	
RH-S10D120HDG	3" x .120"	Smooth	Hot Dipped	Diamond	4000	
RH-S10DR120SS	3" x .120"	Ring	Stainless	Diamond	4000	
RH-S10DR120HDG	3" x .120"	Ring	Hot Dipped	Diamond	4000	
RH-S10D131EP	3" x .131"	Smooth	Coated	Diamond	4000	
RH-S10D131HDG	3" x .131"	Smooth	Hot Dipped	Diamond	4000	
RH-S10DR131EP	3" x .131"	Ring	Coated	Diamond	4000	
RH-S10DR131HDG	3" x .131"	Ring	Hot Dipped	Diamond	4000	
RH-S10DS120HDG	3 x .120"	Screw	Hot Dipped	Diamond	4000	
RH-S12D120EP	3" x .148	Smooth	Coated	Diamond	3000	BOSTITCH® F21PL, F21PL2, N79RH, N88RH- 2MCN, N88RH, N95RHN
RH-S12D120EP	3-1/4" x .120	Smooth	Coated	Diamond	4000	
RH-S12D131EP	3-1/4" x .131	Smooth	Coated	Diamond	4000	
RH-S12D131HDG	3-1/4" x .131	Smooth	Hot Dipped	Diamond	4000	
RH-S12D148EP	3-1/4" x .148	Smooth	Coated	Diamond	3000	
RH-S12DS148EP	3-1/4" x .148	Screw	Coated	Diamond	3000	
RH-S12D162EP	3-1/4" x .162	Smooth	Coated	Diamond	3000	
RH-S16D131EP	3-1/2" x .131	Smooth	Coated	Diamond	4000	
RH-S16D131HDG	3-1/2" x .131	Smooth	Hot Dipped	Diamond	4000	
RH-S16D135EP	3-1/2" x .135	Smooth	Coated	Diamond	2000	
RH-S16D162EP	3-1/2" x .162	Smooth	Coated	Diamond	3000	BOSTITCH® F21PL, F21PL2, N79RH, N88RH- 2MCN, N88RH, N95RHN, N95162
S38-100B	4" x .150	Smooth	Coated	Diamond	1250	BOSTITCH® KN85PP, BIGBERTA160, BRT130
S38-115B	4-1/2" x .150	Smooth	Coated	Diamond	1250	
S34S-115B	4-1/2" x .134	Screw	Coated	Diamond	1250	
S38-130B	5-1/8" x .150	Smooth	Coated	Diamond	1250	
S42-130B	5-1/8" x .165	Smooth	Coated	Diamond		
S42-160B	6-1/4" x .165	Smooth	Coated	Diamond	660	BOSTITCH® BIGBERTA160

ALSO FITS

DEWALT D51845 • DUOFAST CN350B • Hitachi NR83A, MR90AC • Makita AN922, AM8300 • Paslode 5300, F350SRH
Porter-Cable FR350, FR350MAG • Ridgid R350RHA • Senco SCN60, SCN65, SN65C, FramePro FRH



I. 15° Coil Roofing Nails

SKU #	SIZE	SHANK	FINISH	POINT STYLE	QUANTITY	FITS
CR19GAL	3/4"	Smooth	Galvanized	Diamond	7200	BOSTITCH® RN45B, RN46
CR2DCGAL	7/8"	Smooth	Galvanized	Diamond	7200	
CR2DGAL	1"	Smooth	Galvanized	Diamond	7200	
CR3DGAL	1-1/4"	Smooth	Galvanized	Diamond	7200	
CR3DSS	1-1/4"	Smooth	Stainless Steel	Diamond	7200	
CR4DGAL	1-1/2"	Smooth	Galvanized	Diamond	7200	
CR4DSS	1-1/2"	Smooth	Stainless Steel	Diamond	7200	
CR5DGAL	1-3/4"	Smooth	Galvanized	Diamond	7200	
ALSO FITS						
ATRO CN134, Roofing Roll • CRAFTSMAN 18324, 154500 • DEWALT D51321 • Paslode 3175RCU • Hitachi NV45AB, NV45AC, NV45AB2 • Hitachi NV45AB, NV45AC, NV45AB2 • Porter-Cable RN175A • Ridgid R350CHA • Senco SN2+, SN3, SN325+, SN4, SN70, FramePro						

J. 16-Gauge 1" Crown Construction Staples

SKU #	SIZE	CROWN	FINISH	POINT STYLE	QUANTITY	FITS
16S2-16	21/32"	1"	Brite	Chisel	15000	BOSTITCH® 438S2R, 438S2, 450S2, T40S2
16S2-16GAL	21/32"	1"	Galvanized	Chisel	15000	
16S2-19	3/4"	1"	Brite	Chisel	13500	
16S2-19GAL	3/4"	1"	Galvanized	Chisel	13500	
16S2-22	7/8"	1"	Brite	Chisel	12000	
16S2-22GAL	7/8"	1"	Galvanized	Chisel	12000	
16S2-25	1"	1"	Brite	Chisel	10500	
16S2-25GAL	1"	1"	Galvanized	Chisel	10500	
16S2-31	1-1/4"	1"	Brite	Chisel	9000	
16S2-31GAL	1-1/4"	1"	Galvanized	Chisel	9000	
16S2-38	1-1/2"	1"	Brite	Chisel	7500	
16S2-38GAL	1-1/2"	1"	Galvanized	Chisel	7500	
16S2-38SS-1M	1-1/2"	1"	Stainless Steel	Chisel	1050	
16S2-44	1-3/4"	1"	Brite	Chisel	6000	
16S2-44GAL	1-3/4"	1"	Galvanized	Chisel	6000	
16S2-50	2"	1"	Brite	Chisel	6000	
16S2-50GAL	2"	1"	Galvanized	Chisel	6000	

CONSTRUCTION FASTENERS

FINISH & TRIM

K. 15-Gauge "FN" Style Angled Finish Nails

SKU #	SIZE	POINT STYLE	FINISH	QUANTITY	FITS
FN1520-1M	1-1/4"	Chisel	Coated	1000	BOSTITCH® GFN1564K, N59FN, N60FN, N62FNK-2
FN1520	1-1/4"	Chisel	Coated	3655	
FN1524-1M	1-1/2"	Chisel	Coated	1000	
FN1524SS-1M	1-1/2"	Chisel	Stainless	1000	
FN1524	1-1/2"	Chisel	Coated	3655	
FN1528	1-3/4"	Chisel	Coated	3655	
FN1532-1M	2"	Chisel	Coated	1000	
FN1532SS-1M	2"	Chisel	Stainless	1000	
FN1532	2"	Chisel	Coated	3655	
FN1536	2-1/4"	Chisel	Coated	3655	
FN1540-1M	2-1/2"	Chisel	Coated	1000	
FN1540SS-1M	2-1/2"	Chisel	Stainless	1000	
FN1540	2-1/2"	Chisel	Coated	3655	

L. 15-Gauge "DA" Style Angled Finish Nails

SKU #	SIZE	POINT STYLE	FINISH	QUANTITY	FITS
DA-1520	1-1/4"	Chisel	Coated	4000	BOSTITCH® Model Not Available
DA-1524	1-1/2"	Chisel	Coated	4000	
DA-1532	2"	Chisel	Coated	4000	
DA-1540	2-1/2"	Chisel	Coated	4000	

ALSO FITS Porter-Cable DA250C, DA250B, DA250A, Dewalt D51276K, D51275K, DC628K

M. 16-Gauge Straight Finish Nails

SKU #	SIZE	POINT STYLE	FINISH	QUANTITY	FITS
SB16-1.25-1M	1-1/4"	Chisel	Coated	1000	BOSTITCH® GFN1664K, FN16250K, SB-1664FN, FN1664K
SB16-1.5-1M	1-1/2"	Chisel	Coated	1000	
SB1615SS	1-1/2"	Chisel	Stainless	500	
SB16-1.50	1-1/2"	Chisel	Coated	2500	
SB16-1.75-1M	1-3/4"	Chisel	Coated	1000	
SB16-2.00-1M	2"	Chisel	Coated	1000	
SB1620SS	2"	Chisel	Stainless	500	
SB16-2.00	2"	Chisel	Coated	2500	
SB16-2.5-1M	2-1/2"	Chisel	Coated	1000	
SB1625SS	2-1/2"	Chisel	Stainless	500	
SB16-2.50	2-1/2"	Chisel	Coated	2500	

ALSO FITS Porter-Cable FN250C, Dewalt D51257K



N. 18-Gauge Brads

SKU #	SIZE	POINT STYLE	FINISH	QUANTITY	FITS	
BT1300B-1M	5/8"	Chisel	Coated	1000	BOSTITCH® GBT1850K, SB-1850BN, SB-2IN1, BT125K-2, BT200K-2, BT1855K	
BT1300B	5/8"	Chisel	Coated	3000		
BT1303B-1M	3/4"	Chisel	Coated	1000		
BT1303B	3/4"	Chisel	Coated	3000		
BT1309B-1M	1"	Chisel	Coated	1000		
BT1309B	1"	Chisel	Coated	3000		
BT1314B-1M	1-3/16"	Chisel	Coated	1000		
BT1314B	1-3/16"	Chisel	Coated	3000		
BT1332B-1M	1-1/4"	Chisel	Coated	1000		
BT1332SS	1-1/4"	Chisel	Stainless	500		
BT1335B-1M	1-3/8"	Chisel	Coated	1000		
BT1335B	1-3/8"	Chisel	Coated	3000		
BT1338B-1M	1-1/2"	Chisel	Coated	1000		BOSTITCH® GBT1850K, SB-1850BN, SB-2IN1, BT200K-2, BT1855K
BT1338B	1-1/2"	Chisel	Coated	2000		
BT1340B	1-9/16"	Chisel	Coated	2000		
BT1345B-1M	1-3/4"	Chisel	Coated	1000		
BT1345B	1-3/4"	Chisel	Coated	2000		
BT1350B-1M	2"	Chisel	Coated	1000		
BT1350SS	2"	Chisel	Stainless	500		
BT1350B	2"	Chisel	Coated	2000		

ALSO FITS Porter-Cable BN138, BN125A, BN200B, BN200A, Dewalt D51236K, D51238K, DC608K

O. 18-Gauge 7/32" Crown Staples

SKU #	SIZE	CROWN	FINISH	QTY.	FITS
SX50351/2G-7M	1/2"	7/32"	Coated	7000	BOSTITCH® SX1838K, SX150K-1, SB-150SX, SB-2IN1 EHF1838K, S32SX-BHF-2, SX150-BHF-2
SX50355/8G	5/8"	7/32"	Coated	5000	
SX50353/4G	3/4"	7/32"	Coated	5000	
SX50357/8G	7/8"	7/32"	Coated	5000	
SX50351G	1"	7/32"	Coated	5000	
SX50351SS-1M	1"	7/32"	Stainless	1000	
SX50351-1/8G	1-1/8"	7/32"	Coated	3000	
SX50351-3/16G	1-3/16"	7/32"	Coated	3000	
SX50351-1/4G	1-1/4"	7/32"	Coated	3000	
SX50351-3/8G	1-3/8"	7/32"	Coated	3000	
SX50351/2G	1-1/2"	7/32"	Coated	3000	

P. 23-Gauge Pin Nails

SKU #	SIZE	POINT STYLE	FINISH	QUANTITY	FITS
PT-2312-3M	1/2"	Chisel	Coated	3000	BOSTITCH® TU-216-2330, HP118K
PT-2319-3M	3/4"	Chisel	Coated	3000	
PT-2325-3M	1"	Chisel	Coated	3000	
PT-2330-3M	1-3/16"	Chisel	Coated	3000	

ALSO FITS Porter-Cable PIN100, PIN138

CONSTRUCTION FASTENERS

Q. 15.5-Gauge 1/2" Crown Hardwood Flooring Staples

SKU #	SIZE	CROWN	FINISH	POINT STYLE	QUANTITY	FITS
BCS1512	1-1/2"	1/2"	Coated	Chisel	9600	BOSTITCH® MIIIFS
BCS1514	1-3/4"	1/2"	Coated	Chisel	7728	
BCS1516	2"	1/2"	Coated	Chisel	7728	
BCS1516SS-1M	2"	1/2"	Stainless	Chisel	1000	
BCS1516-SQ	2"	1/2"	Coated	Chisel	500	

R. L-Shaped Hardwood Flooring Cleats

SKU #	SIZE	FINISH	QUANTITY	FITS
FLN-150	1-1/2"	Coated	1000	BOSTITCH® MIIIFN, MFN-200, MFN-201
FLN-200	2"	Coated	1000	

S. 20-Gauge Flooring Staple

SKU #	SIZE	CROWN	FINISH	QUANTITY	POINT STYLE	FITS
SB97-1GLS	1"	3/16"	Coated	5000	Chisel	BOSTITCH® LHF2025K, LHF97125-2, S3297-LHF-2

T. 18-Gauge 7/32" Crown Staples

SKU #	SIZE	CROWN	FINISH	QTY.	FITS
SX50351G	1"	7/32"	Coated	5000	BOSTITCH® EHF1838K, S32SX-BHF-2, SX150-BHF-2
SX50351SS-1M	1"	7/32"	Stainless	1000	
SX50351-1/8G	1-1/8"	7/32"	Coated	3000	
SX50351-3/16G	1-3/16"	7/32"	Coated	3000	
SX50351-1/4G	1-1/4"	7/32"	Coated	3000	
SX50351-3/8G	1-3/8"	7/32"	Coated	3000	
SX503511/2G	1-1/2"	7/32"	Coated	3000	



U. 15° Wire Weld Coil Siding Nails

SKU #	SIZE	SHANK	FINISH	POINT STYLE	QUANTITY	FITS	
AC3D080BDP	1-1/4" x .080	Smooth	Coated	Blunt Diamond	14000	BOSTITCH® N63CP, N64C, N66C, N66BC	
AC3DR080BDP	1-1/4" x .080	Ring	Coated	Blunt Diamond	14000		
C3R80BDG	1-1/4" x .080	Ring	Thickcoat®	Blunt Diamond	4200		
AC4D080BDP	1-1/2" x .080	Smooth	Coated	Blunt Diamond	14000		
AC4DR080BDP	1-1/2" x .080	Ring	Coated	Blunt Diamond	14000		
C4R80BDG	1-1/2" x .080	Ring	Thickcoat®	Blunt Diamond	4200		
C4R90BDSS	1-1/2" x .090	Ring	Stainless	Blunt Diamond	3600		
AC5D080BDP	1-3/4" x .080	Smooth	Coated	Blunt Diamond	14000		
AC5DR080BDP	1-3/4" x .080	Ring	Coated	Blunt Diamond	14000		
C5R80BDG	1-3/4" x .080	Ring	Thickcoat®	Blunt Diamond	4200		
C5R90BDSS	1-3/4" x .092	Ring	Stainless	Blunt Diamond	3600		
AC6D090BDP	2" x .092	Smooth	Coated	Blunt Diamond	12000		
C6P90BDG	2" x .092	Smooth	Thickcoat®	Blunt Diamond	3600		
AC6DR090BDP	2" x .092	Ring	Coated	Blunt Diamond	12000		
C6R90BDG	2" x .092	Ring	Thickcoat®	Blunt Diamond	3600		
C6R90BDSS	2" x .092	Ring	Stainless	Blunt Diamond	3600		
C7P90BDG	2-3/16" x .092	Smooth	Thickcoat®	Blunt Diamond	3600		BOSTITCH® N63CP, N64C, N66C, N66BC, N75C
C7R90BDG	2-3/16" x .092	Ring	Thickcoat®	Blunt Diamond	3600		
C7R90BDSS	2-3/16" x .092	Ring	Stainless	Blunt Diamond	3600		
C8P90BDG	2-1/2" x .092	Smooth	Thickcoat®	Blunt Diamond	3600		
C8R90BDG	2-1/2" x .092	Ring	Thickcoat®	Blunt Diamond	3600		
AC8DRSS	2-1/2" x .092	Ring	Stainless	Blunt Diamond	3600		

ALSO FITS Hitachi NV65AH, Max CN565, Makita AN611, Porter-Cable COIL200, COIL250

V. 18-Gauge 5/16" Crown Staples

SKU #	SIZE	CROWN	FINISH	QUANTITY	FITS
SL50351G1M	1"	5/16"	Coated	1000	BOSTITCH® SB150SLBC, SL1838BC

W. Bostitch® Caps

SKU #	DESCRIPTION	QUANTITY	FITS
SB-CAPS	Bostitch® Caps	1000	BOSTITCH® SL1838BC, SB150SLBC, N66BC
CAPPAK-1M	Bostitch® Caps & 1" Staples	1000 each	BOSTITCH® SB150SLBC, SL1838BC
CAPPAK-5M	Bostitch® Caps & 1" Staples	5000 each	

CONSTRUCTION FASTENERS

SPECIALTY

X. 15° Plastic Inserted Coil Siding Nails

SKU #	SIZE	SHANK	FINISH	POINT STYLE	QUANTITY	FITS
ACP5DSALM	1-3/4" x .099"	Screw	Aluminum	Diamond	2400	BOSTITCH® N63CP, N65CP, N66C, N66BC, N75C
ACP6D090BDG	2" x .090"	Ring	Galvanized	Diamond	3600	
ACP7DR090BDG	2-1/4" x .090"	Ring	Electro Galv.	Diamond	3600	
ACP8DR090BDSS	2-1/2" x .090"	Ring	Stainless	Diamond	3600	
ALSO FITS Hitachi NV65AH, Max CN565, Makita AN611, Senco SCN55S						

Y. T-Nails for Drywall Track or Wood into Concrete, Block or Masonry

SKU #	SIZE	SHANK	FINISH	POINT STYLE	QUANTITY	FITS
BT484GXH-2.5M	9/16" x .097"	Hardened/ Coated	Smooth	Diamond	2500	BOSTITCH® M111812CNCT
BT461H-2.5M	5/8" x .097"	Stiff	Smooth	Diamond	2500	
BT461XH-2.5M	5/8" x .097"	Hardened	Smooth	Diamond	2500	
BT488XH-2.5M	3/4" x .097"	Hardened	Smooth	Diamond	2500	
BT490XH-2.5M	1-1/8" x .097"	Hardened	Smooth	Diamond	2500	
BT499H-2.5M	1-3/8" x .097"	Hardened	Smooth	Diamond	2500	
BT493XH-2.5M	1-3/8" x .097"	Stiff	Smooth	Diamond	2500	
BT471XH-2.5M	1-1/2" x .097"	Hardened	Smooth	Diamond	2500	
BT481H-2.5M	2-1/4" x .097"	Stiff	Smooth	Diamond	2500	



Z. 16-Gauge 1/2" Crown Construction Staples

SKU #	SIZE	CROWN	FINISH	POINT	QTY.	FITS
16S4-19	3/4"	1/2"	Brite	Chisel	25650	BOSTITCH® 438S4
16S4-19GAL	3/4"	1/2"	Galvanized	Chisel	25650	
16S4-25	1"	1/2"	Brite	Chisel	19950	BOSTITCH® 438S4, 650S4
16S4-25GAL	1"	1/2"	Galvanized	Chisel	19950	
16S4-31	1-1/4"	1/2"	Brite	Chisel	17100	
16S4-31GAL	1-1/4"	1/2"	Galvanized	Chisel	17100	
16S4-34	1-3/8"	1/2"	Brite	Chisel	14250	
16S4-34GAL	1-3/8"	1/2"	Galvanized	Chisel	14250	
16S4-38	1-1/2"	1/2"	Brite	Chisel	14250	
16S4-38GAL	1-1/2"	1/2"	Galvanized	Chisel	14250	
16S4-38SS-1M	1-1/2"	1/2"	Stainless	Chisel	1050	
16S4-41	1-5/8"	1/2"	Brite	Chisel	11400	
16S4-41GAL	1-5/8"	1/2"	Galvanized	Chisel	14250	BOSTITCH® 650S4
16S4-44	1-3/4"	1/2"	Brite	Chisel	11400	
16S4-44GAL	1-3/4"	1/2"	Galvanized	Chisel	11400	
16S4-50	2"	1/2"	Brite	Chisel	11400	
16S4-50GAL	2"	1/2"	Galvanized	Chisel	11400	

AA. 16-Gauge 7/16" Crown Construction Staples

SKU #	SIZE	CROWN	FINISH	POINT	QTY.	FITS
16S5-44	1-3/4"	7/16"	Brite	Chisel	19800	BOSTITCH® 438S5, 538S5, 650S5, 651S5, T40S5, T50S5
16S5-44GAL	1-3/4"	7/16"	Galvanized	Chisel	16500	
16S5-50	2"	7/16"	Brite	Chisel	16500	
16S5-50GAL	2"	7/16"	Galvanized	Chisel	16500	

BB. Heavy-Duty PowerCrown® Staples

SKU #	WIRE GAUGE	CROWN	LENGTH	QUANTITY	FITS
STCR50191/4-1M	.050" x .019"	7/16"	1/4"	1000	BOSTITCH® T6-8, T6-80C1, PC4000, PC4000C1, PC5000, H30-8, P6C-8, US056-1
STCR50191/4-6M	.050" x .019"	7/16"	1/4"	6000	
STCR50195/16-5M	.050" x .019"	7/16"	5/16"	5000	
STCR50193/8-1M	.050" x .019"	7/16"	3/8"	1000	
STCR50193/8-5M	.050" x .019"	7/16"	3/8"	5000	
STCR50191/2-1M	.050" x .019"	7/16"	1/2"	1000	BOSTITCH® T6-8, T6-80C2, PC3000, PC4000, PC4000C2, PC5000, PC3000, US056-1
STCR50191/2-4M	.050" x .019"	7/16"	1/2"	4000	BOSTITCH® T6-8, T6-80C2, PC4000, PC4000C2, PC5000, US056-1
STCR50199/16-1M	.050" x .019"	7/16"	9/16"	1000	BOSTITCH® T6-8, T6-80C2, US056-1, PC4000, PC4000C2
STCR50199/16-4M	.050" x .019"	7/16"	9/16"	4000	

CC. Light-Duty PowerCrown® Staples

SKU #	WIRE GAUGE	CROWN	LENGTH	QUANTITY	FITS
STCR26191/4	.026" x .019"	7/16"	1/4"	5000	BOSTITCH® T5-6, H30-6, P6C-6
STCR26195/16	.026" x .019"	7/16"	5/16"	5000	
STCR26193/8	.026" x .019"	7/16"	3/8"	5000	T5-6, P6C-6, H30-6
STCR26191/2	.026" x .019"	7/16"	1/2"	5000	T5-6, PC3000C2, T6-60C2


DD. Light-Wire Staples

SKU #	WIRE GAUGE	CROWN	LENGTH	QUANTITY	FITS
SP191/4	.019"	3/8"	1/4"	5000	P3-IND, P3-Chrome




EE. Collated Rings

SKU #	FINISH	WIRE GAUGE	LENGTH	QUANTITY	FITS
RING616G50	Galvanized	16-Gauge	11/16"	2500	BOSTITCH® P7
RING616SS50	Stainless Steel	16-Gauge	11/16"	2500	





THICKNESS



POSURE 1
124
VAL 1

BOSTITCH® www.bostitch.co
BOST

STANLEY
BOSTITCH[®]
www.**BOSTITCH**.com

BOSTITCH
East Greenwich, RI 02818
Customer Service 1-800-556-6696
Fax 1-800-842-9360